# Eaton 20D16Q

Eaton Bussmann series low voltage D fuse, Fast-acting, 500V, 20A, 50 kAIC, Non Indicating, fuse, Class gR, Blue

| | |
|---|---|
| **PRODUCT NAME** | Eaton Bussmann series low voltage D fuse |
| **CATALOG NUMBER** | 20D16Q |
| **UPC** | 051712832328 |
| **PRODUCT LENGTH/DEPTH** | 50 mm |
| **PRODUCT HEIGHT** | 13.2 mm |
| **PRODUCT WIDTH** | 13.2 mm |
| **PRODUCT WEIGHT** | 14.8 g |
| **COMPLIANCES** | CE Marked<br>RoHS Compliant |
| **CERTIFICATIONS** | VDE<br>IEC 60269<br>DIN EN 60269-3 (VDE 0636 Part 30)<br>DIN EN 60269-1 (VDE 0636 Part 10)<br>DIN VDE 0636-301 |

Powering Business Worldwide

| □□□□ | |
|---|---|
| **AMPERAGE RATING** | 20 A |
| **FUSE SIZE** | DI |
| **BREAKING CAPACITY** | 50 kA |
| **CONSTRUCTION SIZE (FUSE INSERTS)** | DI |
| **RATED VOLTAGE AC** | 500 V |
| **CLASS** | Class gR |
| **FUSE TYPE** | D16Q - Fast acting |
| **UTILIZATION CATEGORY** | gR (general purpose semiconductor protection) |
| **ACCESSORY/SPARE PART TYPE** | 20GD16 Blue screw cap gauge piece |
| **COLOR** | Blue |
| **INTERRUPT RATING** | 50 kAIC |
| **FUSE INDICATOR** | Non-indicating |
| **CONNECTION** | Other |
| **CONSTRUCTION** | D1 |
| **CONSTRUCTION SIZE** | DI |
| **FUSE SHAPE** | Bottle |
| **RESPONSE TIME** | Fast-acting |
| **SUITABLE FOR** | E16/DI Fuse base |
| **MATERIAL** | White ceramic body |
| **PACKAGING TYPE** | Standard |
| **RELEASE CHARACTERISTIC** | Fast (F) |
| **VOLTAGE RATING** | 500 V |
| **TYPE** | Fuse |
| **SPECIAL FEATURES** | Fast-acting |
| **APPLICATION** | For domestic and general industrial applications |

| □□ | |
|---|---|
| DECLARATIONS OF CONFORMITY | eaton-low-voltage-d-fuse-declaration-of-conformity-uk251016en.pdf |

| | |
|---|---|
| □□□□: | |
| □□□□: | |
| □□□: | |
| □□: | |

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□