

1	2	3	4	5	6	7	8	
				REV.	ECN NO.	DATE	SIGN	DESCRIPTION

Panel Thickness
面板厚度
X(Max.)

Screw L=5.0 For Panel Thickness
Under 1.2mm
適用板厚為1.2mm以下

Screw L=6.0 For Panel Thickness
Between 1.2~2.0mm
適用板厚為1.2~2.0mm

26 Pin Male connector
PCB Pin Layout
Scale 2:1

ALTW
DCC. DEPT.
CONFIDENTIAL
2007.01.22
ISSUED

ALTW
CONFIDENTIAL
2006.12.09
R&D DEPT.

Note:
* @C Important Dimension.
* Waterproof Rate : IP68
IP68:1M of depth of water 24 hours
(防水等級 IP68)
(IP68:1米水深 24小時)
* Do Mating Test After Glued
點膠後,須作對插測試
* HD-SUB Conn. :Black Core , PBT
* Plastic Jacket : Black , Nylon+GF
* Pin : Copper Alloy , Gold Plated
* Ring : Light Blue,Silicone
* Screw : Copper Alloy,Nickel Plated,#4-40 UNC

UNIT:mm		TITLE D-SUB Conn.
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°	Panel Screw HD26P M Conn. M Pin	
SCALE Free	SHEET 1 OF 1	
REV. A	SIZE A4	@C :Inspection Item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO HDB-26PMMP-SR8001	DRAWN BY Gao Ling	DATE 2006/12/09
DWG NO HDB-26PMMP-SR8001	CHECKED BY Simon	DATE 2006/12/09
CUSTOMER ALTW	APPROVED BY Max	DATE 2006/12/09

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

8 FMWIO702-01-01A2