# Eaton 170M5374

Fuse-link, high speed, 630 A, AC 1250 V, size 2, 59 x 59 x 150 mm, aR, IEC, single indicator

| | |
|---|---|
| **PRODUCT NAME** | Eaton Bussmann series high speed square body fuse |
| **CATALOG NUMBER** | 170M5374 |
| **UPC** | 051712248440 |
| **PRODUCT LENGTH/DEPTH** | 150 mm |
| **PRODUCT HEIGHT** | 69 mm |
| **PRODUCT WIDTH** | 59 mm |
| **PRODUCT WEIGHT** | 746 g |
| **COMPLIANCES** | Contact factory<br>RoHS Compliant |

Powering Business Worldwide

| □□□□ | |
|---|---|
| **AMPERAGE RATING** | 630 A |
| **BREAKING CAPACITY** | 100 kA |
| **FUSE INDICATOR** | Top fuse status indicator |
| **INSULATED METAL GRIPPING LUGS (IMGL)** | No |
| **UTILIZATION CATEGORY** | aR (accompanied semiconductor protection) |
| **VOLTAGE TYPE** | AC |
| **FUSE SIZE** | 2 |
| **RATED VOLTAGE AC** | 1250 V |
| **CURRENT TYPE** | AC |
| **CLASS** | Class aR |
| **WATT LOSSES** | 110 W |
| **FUSE SHAPE** | Square body, special bladed contacts |
| **COLOR** | None |
| **INTERRUPT RATING** | 100 kAIC |
| **CONSTRUCTION SIZE** | 2 |
| **PACKAGING TYPE** | Standard |
| **VOLTAGE RATING** | 1250 V |
| **TYPE** | Fuse |
| **APPLICATION** | semiconductor protection |
| **FUSE TYPE** | T indicator for micro |
| **FUSE SYSTEM (ACCORDING TO IEC 60269)** | Other |

| □□ | |
|---|---|
| DECLARATIONS OF CONFORMITY | eaton-high-speed-square-body-fuse-declaration-of-conformity-uk251153en.pdf |

| | |
|---|---|
| **□□□□:** | |
| **□□□□:** | |
| **□□□:** | |
| **□□:** | |

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□