Eaton FCF20RN

Eaton Bussmann Series UL Class CF, FCF fuse, fast-acting, single-element cube fuse, 20 A, non-idicating fuse, interrupting rating of 50 kA at 600 Vdc and 300 kA at 600 Vac

PRODUCT NAME	Eaton Bussmann series FCF fuse
CATALOG NUMBER	FCF20RN
UPC	051712362467
PRODUCT LENGTH/DEPTH	1.88 in
PRODUCT HEIGHT	1.75 in
PRODUCT WIDTH	0.75 in
PRODUCT WEIGHT	0.08 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Listed CSA Certified

Powering Business Worldwide

□□□□□

AMPERAGE RATING	20 A
FREQUENCY RATING - MAX	60 Hz
FREQUENCY RATING - MIN	50 Hz
INTERRUPT RATING	300 kAIC at 600 Vac 50 kAIC at 600 Vdc
RESPONSE TIME	4 min at 200%
VOLTAGE RATING	600 Vac, 600 Vdc

□□□□□□

COLOR	Black
FUSE TYPE	Class CF Fast acting
MATERIAL	Glass filled PES
NUMBER OF ELEMENTS	1
OPERATING TEMPERATURE	-40° to 80°C
PACKAGING TYPE	Standard
TERMINAL MATERIAL	Electroless tin plated copper alloy terminal

□□□□

CLASS	Class CF
CONNECTION	Blade end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Superior overload and cycling capabilities
USED WITH	TCFH30N, CCP2-3-30CF

□□

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□