# Specifications







## Eaton CS6369

Eaton locking receptacle, #10-6 AWG, 50A, Industrial, 125/250V, Back wiring, Black, Single, Non-NEMA, Three-pole, Four-wire, Steel, California standard

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton Arrow Hart California standard locking receptacle |
| **CATALOG NUMBER** | CS6369 |
| **UPC** | 040893674834 |
| **PRODUCT LENGTH/DEPTH** | 6.25 in |
| **PRODUCT HEIGHT** | 3.25 in |
| **PRODUCT WIDTH** | 3 in |
| **PRODUCT WEIGHT** | 0.79 lb |
| **COMPLIANCES** | RoHS Compliant |
| **CERTIFICATIONS** | CSA certified<br>UL Listed<br>cULus Listed |
| **PRODUCT TYPE** | California standard |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **SPECIAL FEATURES** | Locking plug |
| **TYPE** | Locking receptacle |
| **AMPERAGE RATING** | 50 A |
| **VOLTAGE RATING** | 125/250 V |
| **CONTACT MATERIAL** | Zinc plated brass |
| **APPLICATION** | Industrial |
| **DEVICE GRADE** | Extra heavy duty |
| **WIRING METHOD** | Back |
| **NUMBER OF WIRES** | 4<br>Grounding |
| **NUMBER OF POLES** | Three-pole |
| **COLOR** | Black |
| **MATERIAL** | Steel |
| **OPERATING TEMPERATURE** | -40 to 105 °C (-40 to 221 °F) |
| **STANDARD** | California standard |
| **ALLOWABLE WIRE SIZE** | #10-6 AWG |
| **NEMA CONFIGURATION** | Non-NEMA |
| **TORQUE RATING** | 45 lbf-inch |
| **DESIGN TYPE** | Single receptacle |
| **FACE/BODY MATERIAL** | Glass filled nylon |
| **RECEPTACLE TYPE** | Locking |

## Resources

| | |
|---|---|
| MULTIMEDIA | Arrow Hart - Connecting Safety to Reliability since 1890 |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - CS6369<br>Hart lock industrial grade 50A locking devices spec sheet<br>Industrial grade 50A locking devices spec sheet |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.