MELCHER™

LRS Series

AC-DC Subrack System MK007



MK007 is a power supply system designed for railway and subway application. The applicable railway standards, mainly EN 50155, EN 50121-4, and the respective AREMA standards are observed. The power supply system is designed to accommodate special LK converters, such as LK5542-9ERD8TG or LK5662-9ERD8TG.

A main feature is the enhanced voltage isolation (3000 VAC) between outputs, alarm signals, and the metallic chassis respectively the ground.

The system consists of one or two racks. Each rack can accommodate up to 4 converters, which allows redundant configuration in terms of input and output energy.

A floating relay contact is available to monitor the function of each converter.

5 YEAR warranty

Features

- Compliant to AREMA, EN 50155, and EN 50121-4
- RoHS-compliant for all 6 substances
- 5 year warranty
- 19-inch rack system, convection cooling
- Different output configurations
- Extremely rugged, reliable design for harsh environment
- Class I equipment
- Extremely high isolation of all output circuits
- Excellent surge and transient protection
- Wide input voltage range 85 to 264 VAC, 50 to 60 Hz
- Power factor >0.93, harmonics IEC/EN 61000-3-2
- Output voltage adjust
- Active output current sharing
- Output voltage monitor with relay contacts
- Inrush current limitation
- PCBs with conformal coating – except PCBs of the rack
- Hot swappable
- Safety-approved to the latest edition of IEC/EN 62368-1 and UL/CSA 60950-1.

Table of Contents

	Page
Description	1
Model Selection	2
Functional Description	5
Electrical Input Data	7
Electrical Output Data	9
Electromagnetic Compatibility (EMC)	12
Immunity to Environmental Conditions	13
Mechanical Data	14
Safety and Installation Instructions	17
Accessories	18

bel POWER | PROTECT | CONNECT

Please read our datasheet & drawing disclaimer here.

Model Selection

The system consists of converters and racks.

Table 1: Converters. Other output configurations or special customer adaptations are available on request.

Output 1		Output 2		Operating input range		Type designation	Efficiency	
$V_{o\,nom}$ [VDC]	$I_{o\,nom}$ [A]	$V_{o\,nom}$ [VDC]	$I_{o\,nom}$ [A]	$V_{i\,min} – V_{i\,max}$ [VAC]	$f_{i\,min} – f_{i\,max}$ [Hz]		η_{min} [1] [%]	η_{typ} [%]
15	5	15 [2]	5	85 – 264	47 – 63 [3]	LK5542-9ERD8TG	83	85
24	3	24 [2]	3	85 – 264	47 – 63 [3]	LK5662-9ERD8TG	82	84






1 Min. efficiency at V_i = 230 V, $I_{o\,nom}$ and T_A = 25 °C
2 Second output semi-regulated
3 Operating frequencies >60 Hz are possible with some restrictions; see web data sheet of the LK PFC Series (BCD20002-G).

© 2025 Bel Fuse Inc.

LRS Series

AC-DC Subrack System MK007


Table 2a: Single output systems (see Fig. 2a). Other configurations or special customer adaptations are available on request.

Type designation of the system		Output current		Redundancy	Population	Configuration of the converters in the rack [1]
		$V_{o\ nom}$	$I_{o\ nom}$			
MK007-001G – for LK5542 MK007-100G – for LK5662 (Rack with backplane, but without converters)						
Subrack Systems	LRS10-12-900G	1 x 12 V	1 x 10 A	no	1x LK5542 [4]	
	LRS10-15-900G	1 x 15 V	1 x 10 A	no	1x LK5542	
	LRS06-24-900G	1 x 24 V	1 x 6 A	no	1x LK5662	
	LRS05-28-900G	1 x 28 V	1 x 5 A	no	1x LK5542 [3]	
	LRS05-30-900G	1 x 30 V	1 x 5 A	no	1x LK5542	
	LRS03-48-900G	1 x 48 V	1 x 3 A	no	1x LK5662	
	LRS03-50-900G	1 x 50 V	1 x 3 A	no	1x LK5662	
	LRS20-12-900G	1 x 12 V	1 x 20 A	no	2x LK5542 [4]	
	LRS20-15-900G	1 x 15 V	1 x 20 A	no	2x LK5542	
	LRS12-24-900G	1 x 24 V	1 x 12 A	no	2x LK5662	
	LRS10-28-900G	1 x 28 V	1 x 10 A	no	2x LK5542 [3]	
	LRS10-30-900G	1 x 30 V	1 x 10 A	no	2x LK5542	
	LRS06-48-900G	1 x 48 V	1 x 6 A	no	2x LK5662	
	LRS06-50-900G	1 x 50 V	1 x 6 A	no	2x LK5662	
	LRS10-12-901G	2 x 12 V	2 x 10 A	yes	2x LK5542 [4]	
	LRS10-15-901G	2 x 15 V	2 x 10 A	yes	2x LK5542	
	LRS06-24-901G	2 x 24 V	2 x 6 A	yes	2x LK5662	
	LRS05-28-901G	2 x 28 V	2 x 5 A	yes	2x LK5542 [3]	
	LRS05-30-901G	2 x 30 V	2 x 5 A	yes	2x LK554[2]	
	LRS03-48-901G	2 x 48 V	2 x 3 A	yes	2x LK5662	
	LRS03-50-901G	2 x 50 V	2 x 3 A	yes	2x LK5662	
	LRS30-12-900G	1 x 12 V	1 x 30 A	no [2]	3x LK5542 [4]	
	LRS30-15-900G	1 x 15 V	1 x 30 A	no [2]	3x LK5542	
	LRS18-24-900G	1 x 24 V	1 x 18 A	no [2]	3x LK5662	
	LRS15-28-900G	1 x 28 V	1 x15 A	no [2]	3x LK5542 [3]	
	LRS15-30-900G	1 x 30 V	1 x15 A	no [2]	3x LK5542	
	LRS09-48-900G	1 x 48 V	1 x 9 A	no [2]	3x LK5662	
	LRS09-50-900G	1 x 50 V	1 x 9 A	no [2]	3x LK5662	
	LRS20-12-901G	2 x 12 V	2 x 20 A	yes	4x LK5542 [4]	
	LRS20-15-901G	2 x 15 V	2 x 20 A	yes	4x LK5542	
	LRS12-24-901G	2 x 24 V	2 x 12 A	yes	4x LK5662	
	LRS10-28-901G	2 x 28 V	2 x 10 A	yes	4x LK5542 [3]	
	LRS10-30-901G	2 x 30 V	2 x 10 A	yes	4x LK5542	
	LRS06-48-901G	2 x 48 V	2 x 6 A	yes	4x LK5662	
	LRS06-50-901G	2 x 50 V	2 x 6 A	yes	4x LK5662	
	LRS40-12-900G	1 x 12 V	1 x 40 A	no [2]	4x LK5542 [4]	
	LRS40-15-900G	1 x 15 V	1 x 40 A	no [2]	4x LK5542	
	LRS24-24-900G	1 x 24 V	1 x 24 A	no [2]	4x LK5662	
	LRS20-28-900G	1 x 28 V	1 x 20 A	no [2]	4x LK5542 [3]	
	LRS20-30-900G	1 x 30 V	1 x 20 A	no [2]	4x LK5542 [3]	
	LRS12-48-900G	1 x 48 V	1 x 12 A	no [2]	4x LK5662	
	LRS12-50-900G	1 x 50 V	1 x 12 A	no [2]	4x LK5662	

[1] Positions without converter are covered with blank panels
[2] Connect output A and B in parallel
[3] Converters LK5542 with both output in series connection, trimmed to 14 V
[4] Converters LK5542 trimmed to 12 V

© 2025 Bel Fuse Inc.

Table 2b: Dual output systems (see Fig. 2b). Other configurations or special customer adaptations are available on request.

Type designation of the system	Output current		Redundancy	AC input connection	Population	Configuration of the converters in the rack [1]
	$V_{o\ nom}$	$I_{o\ nom}$				
MK007-200G (Rack with backplane, but without converters)						
LRS0506-3024-951G [2]	1 x 30 V (± 15 V) 1 x 24 V	1 x 5 A (2x 5 A) 1 x 6 A	yes	A: L~ :Pos2, Pos3 B: L~ :Pos1, Pos4 magenta connection	2 x LK5542 2 x LK5662	

[1] Positions without converter are covered with blank panels
[2] With customer-specific logos
[3] Converters LK5542 with both output in series connection, trimmed to 14 V

Part Number Description for Single Output System

LRS 20 - 15 -9 0 1 Sxxx G

Series (product family).....LRS
Output current..... 05, 06, 10, 12, 15, 20, 30, 40
Output voltage 12, 15, 24, 28, 30, 48, 50
Operating ambient temperature range
T_A = –40 to +71 °C ..... -9
Options: Bel Power logo on front panel.....0
Custom logo on front panel.....5
Features: Redundancy (no, yes)..... 0, 1
Customer specific model.....Sxxx[1]
RoHS-compliant for all 6 substances .....G

[1] Applicable for non safety critical deviations. xxx are 3 digits assigned for each customer-specific model

Part Number Description for Dual Output System

LRS 05 06 - 30 24 - 9 5 1 G

Series (product family).....LRS
Output current IoA 05, 06, 10, 12, 15, 20, 30, 40
IoB 05, 06, 10, 12, 15, 20, 30, 40
Output voltage VoA..... 15, 24, 28, 30, 48, 50
VoB..... 15, 24, 28, 30, 48, 50
Operating ambient temperature range
T_A = –40 to +71 °C ..... -9
Options: Bel Power logo on front panel.....0
Custom logo on front panel.....5
Features: Redundancy (no, yes)..... 0, 1
Customer specific model.....Sxxx[1]
RoHS-compliant for all 6 substances .....G

[1] Applicable for non safety critical deviations. xxx are 3 digits assigned for each customer-specific model

Asia-Pacific +86 755 298 85888
EMEA +353 61 531 820
North America +1 866 513 2839
powersupport@belf.com
belfuse.com

© 2025 Bel Fuse Inc.


Functional Description

The input voltage is supplied to up to 4 converters type LK5542/LK5662. The outputs of 2 converters in each half of rack are connected together through OR-ing diodes. These 2 converters share their output current evenly due their current share feature.

The converters LK5542 has two outputs with 15 V and the LK5662 have two outputs with 24 V, which can be connected in parallel or in series. The connection of the outputs is done in the factory by the output voltage selector on the backplane. The output voltage can be adjusted by an external resistor located in the backplane (one resistor per converter) in the range of 80 to 110% of the output voltage.

The output voltage is monitored in each converter. When the output voltage is in range, a relay with an isolated contact is activated. All relay contacts are connected to the alarm signal connectors.

The redundancy of the whole system is depending on the numbers of the converters; see Table 2.



1 Transient suppressor (VDR)
2 Inrush current limiter (with opt. E)
3 Bulk capacitor

Fig. 1
Block diagram of a converter

© 2025 Bel Fuse Inc.




Fig. 2a - Single output system
Block diagram of the rack. The converters in the different positions are fitted depending on the configuration; see table 2.
The green connections are valid for the parallel configuration with 15 V or 24 V output, the red connections for serial configuration with 28 V or 50 V output. For details of contacts and wires, see Mechanical Data.
T Share jumper between sections A and B is fitted on models -900G only.




Fig. 2b Dual output system
Block diagram of the rack. The converters in the different positions are fitted depending on the configuration; see table 2.
Section A & B: The magenta connection is valid for operation on two independent AC input voltages. Cyan connection is valid for operation on one single AC input voltage.
Section A: The orange connection is valid for ± Vo symmetric connection (Com terminal).
Section B: The green connections are valid for the parallel configuration with 15 V or 24 V output, the red connections for serial configuration with 28 V, 30 V, 48V or 50 V output. For details of contacts and wires, see Mechanical Data.
T Share jumper between sections A and B is fitted on models -900G only.

© 2025 Bel Fuse Inc.

Electrical Input Data

General Conditions:

– T_A = 25 °C, unless T_C is specified.
– Pin 18 connected to pin 14, R input not connected.

Table 3: Electrical input data per converter

Input			LK5542-9ERD8TG			LK5662-9ERD8TG			Unit
Characteristics		Conditions	min	typ	max	min	typ	max	
V_i	Rated input voltage range	I_o = 0 – $I_{o\,nom}$ $T_{C\,min}$ to $T_{C\,max}$	100		240	100		240	VAC[1]
$V_{i\,op}$	Operating input voltage range		85		264	85		264	
$V_{i\,nom}$	Nominal input voltage	50 – 60 Hz [1]		115 / 230			115 / 230		
I_i	Input current per converter	V_i = 230 V, $I_{o\,nom}$ [2]		0.8			0.8		A
P_{i0}	No-load input power per converter	$V_{i\,min}$ – $V_{i\,max}$, I_o = 0		9	12		9	12	W
C_b	Input capacitance per converter		100	150	180	100	150	180	µF
$V_{i\,abs}$	Input voltage limits without damage				283			283	VAC
			-400		400 [3]	-400		400 [3]	VDC[3]

[1] Rated input frequency: 50 – 60 Hz, operating input frequency: 47 – 63 Hz. Higher frequencies are possible with some restrictions; see web data sheet of the LK PFC Series (BCD20002)
[2] Outputs loaded with $I_{o\,nom}$
[3] For ≤ 1 s.

Input Fuse and Protection of the Converters

A VDR together with the input fuse and a symmetrical input filter form an effective protection against high input transient voltages.

Input fuse: slow-blow, SP T, 4 A, 250 V, 5 × 20 mm

Input Under-/Overvoltage Lockout

If the input voltage remains below approx. 65 VAC or exceeds $V_{i\,abs}$, an internally generated inhibit signal disables the outputs. Do not check the overvoltage lockout function!

If V_i is below $V_{i\,min}$, but above the undervoltage lockout level, the output voltage may be below the value specified in the tables *Electrical Output Data*.

Power Factor and Harmonics

Power factor correction is achieved by controlling the input current waveform synchronously with the input voltage waveform. The power factor control is active under all operating conditions.

Harmonic distortions are below the limits specified in IEC/EN 61000-3-2, class D.




Fig. 3
Power factor versus output current

© 2025 Bel Fuse Inc.

Efficiency




Fig. 4
Efficiency versus output current

Hold-up time




Fig. 5
Hold-up time versus output power

Inrush Current Limitation

The converters exhibit an electronic circuit to limit the inrush current at switch-on.

Note: Subsequent switch-on cycles at start-up are limited to max. 10 cycles during the first 20 seconds (cold converter) and then to max. 1 cycle every 8 s.




Fig. 6
Inrush current limtation, schematic diagram

Table 4: Inrush current characteristics per converter

Characteristics V_i = 230 VAC		Inrush current			Unit
		min	typ	max	
$I_{inr\ p}$	Peak inrush current		–	25.3	A
t_{inr}	Inrush current duration		35	50	ms

© 2025 Bel Fuse Inc.

Electrical Output Data

Table 5a: Output data of the converter

Model			LK5542 Output 1 + 2 in series			LK5662 Output 1 + 2 in series			Unit
Characteristics		Conditions	min	typ	max	min	typ	max	
V_o	Output voltage	$V_{i\,nom}$, $I_{o\,nom}$		30 (28) [1]			48 (50) [1]		V
$I_{o\,nom}$	Output current nom.	$V_{i\,min} - V_{i\,max}$ $T_{C\,min} - T_{C\,max}$		5.0			3.0		A
I_{oL}	Output current limit	$V_{i\,min} - V_{i\,max}$	5.2			3.2			
$\Delta V_{o\,u}$	Static line regulation with respect to $V_{i\,nom}$	$V_{i\,min} - V_{i\,max}$ $I_{o\,nom}$			±30			±40	mV
$\Delta V_{o\,l}$	Static load regulation[1]	$V_{i\,nom}$ (0.1 - 1) $I_{o\,nom}$			–100			–100	
α_{vo}	Temperature coefficient of output voltage	$T_{C\,min} - T_{C\,max}$ $I_{o\,nom}$		±0.02			±0.02		%/K

[1] Output voltage adjusted on the backplane of the rack.

Table 5b: Output data of the converter

Model			LK5542 Output 1 + 2 in parallel			LK5662 Output 1 + 2 in parallel			Unit
Characteristics		Conditions	min	typ	max	min	typ	max	
V_o	Output voltage	$V_{i\,nom}$, $I_{o\,nom}$		15			24		V
$I_{o\,nom}$	Output current nom.	$V_{i\,min} - V_{i\,max}$ $T_{C\,min} - T_{C\,max}$		10			6.0		A
I_{oL}	Output current limit	$V_{i\,min} - V_{i\,max}$	10.4			6.4			
$\Delta V_{o\,u}$	Static line regulation with respect to $V_{i\,nom}$	$V_{i\,min} - V_{i\,max}$ $I_{o\,nom}$			±15			±25	mV
$\Delta V_{o\,l}$	Static load regulation[1]	$V_{i\,nom}$ (0.1 - 1) $I_{o\,nom}$			–60			–100	
α_{vo}	Temperature coefficient of output voltage	$T_{C\,min} - T_{C\,max}$ $I_{o\,nom}$		±0.02			±0.02		%/K

Thermal Protection of the Converters

A temperature sensor generates an internal inhibit signal, which disables the outputs when the case temperature exceeds the value $T_{C\,max}$. The outputs automatically recover, when the temperature drops below this limit.

Continuous operation under simultaneous extreme worst-case conditions of the following three parameters should be avoided: Minimum input voltage, maximum output power, and maximum temperature.

Output Protection of the Converters

Each output is protected by a suppressor diode against overvoltage, which could occur due to a failure of the control circuit. In such a case, the suppressor diode becomes a short circuit and $V_o = 0$. A short circuit at any of the two outputs will cause a shutdown of the other output. A red LED indicates any overload condition.

Asia-Pacific
+86 755 298 85888
EMEA
+353 61 531 820
North America
+1 866 513 2839
powersupport@belf.com
belfuse.com

© 2025 Bel Fuse Inc.

Output Voltage Regulation of the Converters

The following figures apply to double-output models with parallel-connected outputs.




Fig. 7. Typical output characteristic V_o versus I_o.

Output Voltage Monitor of the Converters

An output undervoltage monitoring circuit (D8) is integrated to each converter. A logic “high” signal (NPN output) is generated at the D output (pin 20), when the monitored voltage Vo1–drops below the preselected threshold level V_t. This signal is referenced to S–/Vo1–. The D output recovers, when the monitored voltages exceed $V_t + V_h$. The threshold level is adjusted in the factory to a fixed value suitable for the application.

This output activates a relay located on the backplane MK007 with a floating contact, which is closed when the output voltage of the respective converter is present.

Output Voltage Adjust of the Converters

The control input R (pin 16) allows for adjusting the output voltage by means of an external resistor. When pin 16 is not connected, the output voltage is set to $V_{o\,nom}$. If the converters are inserted in the rack, use Rinc or Rdec according to fig. 13.

Note: Only 1 converter can be adjusted at once. Pull out all other converters, to adjust the first one, then repeat this procedure with all other converters.

Depending on the value of the required output voltage, the resistor must be connected:

either between pin 16 and pin 14 ($V_o < V_{o\,nom}$) to achieve an output voltage adjustment range of approximately 0 – 100% of $V_{o\,nom}$. If the converter is in the rack, use **Rdec** (fig. 13).

or between pin 16 and pin 12 ($V_o > V_{o\,nom}$) to achieve an output voltage adjustment range of 100 – 110% of $V_{o\,nom}$. If the converter is in the rack, use **Rinc** (fig. 13).

The second output of double-output models follows the value of the controlled main output.


Current Sharing between Converters

This feature ensures that the output currents are approximately shared between all parallel-connected converters, hence increasing system reliability. To use this facility, simply interconnect the T pins of all converters and make sure that the references for the T signal (Vo1–, pin 14) are also connected together.

Asia-Pacific
+86 755 298 85888
EMEA
+353 61 531 820
North America
+1 866 513 2839
powersupport@belf.com
belfuse.com

© 2025 Bel Fuse Inc.

Display Status of LEDs



LEDs "OK", "i" and "$I_{o\ L}$" status versus input voltage
Conditions: $I_o \le I_{o\ nom}$, $T_C \le T_{C\ max}$, $V_{inh} \le 0.8$ V
$V_{i\ uv}$ = undervoltage lock-out, $V_{i\ ov}$ = overvoltage lock-out

LEDs "OK" and "$I_{o\ L}$" status versus output current
Conditions: $V_{i\ min} - V_{i\ max}$, $T_C \le T_{C\ max}$, $V_{inh} \le 0.8$ V

LED "i" versus case temperature
Conditions: $V_{i\ min} - V_{i\ max}$, $I_o \le I_{o\ nom}$, $V_{inh} \le 0.8$ V

LED "i" versus V_{inh}
Conditions: $V_{i\ min} - V_{i\ max}$, $I_o \le I_{o\ nom}$, $T_C \le T_{C\ max}$

Fig.8
LED indicators

© 2025 Bel Fuse Inc.

Electromagnetic Compatibility (EMC)

The **converters** and populated **subrack systems** successfully been tested to the following specifications:

Immunity

Table 7: Electromagnetic immunity (type tests)

Phenomenon	Standard	Level	Coupling mode [1]	Value applied	Waveform	Source imped.	Test procedure	In oper.	Perf. crit. [2]
Electrostatic discharge (to case)	IEC/EN 61000-4-2	4	contact discharge	8000 V_p	1/50 ns	330 W 150 pF	10 positive and 10 negative discharges	yes	A
			air discharge	15000 V_p					
Electromagnetic field / Radiated susceptibility	IEC/EN 61000-4-3	3	antenna	20 V/m	AM 80%, 1 kHz	N/A	80 MHz – 1 GHz	yes	A
				10 V/m			1.4 – 2.1 GHz		
				5 V/m			2.1 – 2.5 GHz		
Electrical fast transients/burst	IEC/EN 61000-4-4	3	capacitive, o/c	±2000 V_p	bursts of 5/50 ns 2.5/5 kHz over 15 ms; burst period: 300 ms	50 Ω	60 s positive 60 s negative transients per coupling mode	yes	A
			±i/c, +i/–i direct						
Surges	IEC/EN 61000-4-5	3	±i/c	±2000 V_p	1.2/50 µs	12 Ω	5 pos. & 5 neg. surges per coupling mode	yes	A
			+i/–i			2 Ω			
Conducted disturbances	IEC/EN 61000-4-6	3	i, o, signal wires	10 VAC (140 dBµV)	AM 80% 1 kHz	150 Ω	0.15 – 80 MHz sine wave	yes	A

[1] i = input, o = output, c = case
[2] A = Normal operation, no deviation from specifications, B = Temporary loss of function or deviation from specs.

Emissions

For conducted emissions, the **converters** comply with class A according to EN 55032 and FCC Part 15.
For radiated emissions, the converters comply with class A according to EN 55032 and FCC Part 15 (30 MHz – 10 GHz).
The populated subrack systems have been tested for conducted and radiated emissions; see fig. 9 and fig. 10.




Fig. 9
Conducted emissions peak and average at the input (populated subrack system LRS40-15-900G at V_{in} = 230 VAC, V_o = 15 V, I_o = 40 A)




Fig.10
Radiated emissions quasi peak, antenna distance 10 m (populated subrack system LRS40-15-900G at V_{in} = 230 VAC, V_o = 15 V, I_o = 40 A)

© 2025 Bel Fuse Inc.

Immunity to Environmental Conditions

The populated subrack system has been tested as per table 8.

Table 8: Mechanical and climatic stress for a populated rack

Test method		Standard	Test Conditions		Operating Condition
Cab	Damp heat steady state	IEC/EN 60068-2-78:2001 MIL-STD-810D section 507.2	Temperature:	40 $^{\pm 2}$ °C	System incl. converters not operating
			Relative humidity:	93 $^{+2/-3}$ %	
			Duration:	56 days	
Kb	Salt mist, cyclic (sodium chloride NaCl solution)	IEC/EN 60068-2-52:1996	Concentration:	5% (30 °C) for 2 h per cycle	System incl. converters not operating
			Storage:	40°C, 93% rel. humidity for	
			Duration:	3 cycles of 22 h	
Fc	Vibration (sinusoidal)	AREMA Part. 11.5.1 class B (wayside outdoors)	Acceleration amplitude:	2.54 mm (5 – 20 Hz) 2 g_n = 19.6 m/s^2 (20 – 200 Hz)	System incl. converters operating
			Frequency (0.9 Oct/min):	5 – 200 Hz	
			Test duration:	12 h (4 h in each axis)	
Ea	Shock (half-sinusoidal)	AREMA Part. 11.5.1 class B (wayside outdoors)	Acceleration amplitude:	10 g_n = 98 m/s^2	System incl. converters operating
			Bump duration:	11 ms	
			Number of bumps:	18 (3 in each direction)	

The converters have been tested separately to more severe limits and with more tests. For details, see K Series Data Sheet on our web site (BCD20001-G).

Temperatures

Table 9: Temperature specifications

Temperature characteristics		Conditions	-9			Unit
			min	typ	max	
T_A	Ambient temperature [1]	Converter operating	–40		+71 [1]	° C
T_C	Case temperature [2]		–40		+95 [2]	
T_S	Storage temperature	Non operational	–55		+95 [2]	

[1] For converters and the systems
[2] For converters. Overtemperature lockout at T_C >95 °C

Asia-Pacific
+86 755 298 85888
EMEA
+353 61 531 820
North America
+1 866 513 2839
powersupport@belf.com
belfuse.com

© 2025 Bel Fuse Inc.

Mechanical Data

Dimensions in mm. The converters are designed to be inserted into a 19” rack, 160 mm long, according to IEC 60297-3.




Fig. 11
Converter with mounted front plate and handle.
Aluminum case K02 with heat sink, black finish (EP powder coated).
Total weight approx. 1.8 kg.

Note: Weight of a blanc panel is 0.15 kg.

© 2025 Bel Fuse Inc.




Fig. 12

19” rack MK007-001G, dimensions in mm.

Weight approx. 2.8 kg (empty)

© 2025 Bel Fuse Inc.




Fig. 13a: Rear view and connections of single output system.
"W-" stands for "WAGO 745-". Recommended cable cross sections; see Table 11 for min / max cross sections.




Fig. 13b: Rear view and connections of dual output system.
"W-" stands for "WAGO 745-". Recommended cable cross sections; see Table 11 for min / max cross sections.

Table 10: Allocation of resistors for output voltage adjustment

Designation	Function
R3 / R9 / Vo+ / Rinc	Increasing output voltage
R4 / R10 / Vo- / Rdec	Decreasing output voltage

© 2025 Bel Fuse Inc.

Safety and Installation Instructions

Please read the Installation Instruction **BCM.00071**.

Table 11: Cross sections

Position	WAGO reference	Cross section		
		min	recom	max
Input / Output	745-851, 745-854	24 AWG	12 AWG	6 AWG
PE ⏚	745-857	24 AWG	8 AWG	6 AWG
Alarm signals	745-857	24 AWG	16 AWG	12 AWG

Connector Pin Allocation of the Converters

The connector pin allocation table defines the electrical potentials and the physical pin positions on the H15 connector.




Fig. 14
View of converter's male connector, type H15

Table 12: Pin allocation of the converter

Pin	LK5542, LK5662	
4, 6	Vo2+	Pos. output 2
8, 10	Vo2–	Neg. output 2
12	Vo1+	Pos. output 1
14	Vo1–	Neg. output 1
16	R	Control of V_{o1}
18	i	Inhibit
20	D	Save data
22	T	Current share
24 [1]	⏚	Protective earth PE
26, 28	N~	Neutral line
30, 32	L~	Phase line

[1] Leading pin (pre-connecting)

The protective earth is connected by a leading pin (no. 24), ensuring that it makes contact with the female connector first.

Standards and Approvals

The **converters** correspond to Class I equipment and are safety-approved to the latest edition of IEC/EN 62368-1 and UL/CSA 60950-1. For more details see the special data sheets of LK5442 and LK5662 and the LK PFC Series on our web site.

All products are subject to manufacturing surveillance in accordance with the above mentioned standards and with ISO 9001:2015, IRIS ISO/TS 22163:2017 certified quality and business management system.

Touch Current

Touch current flow due to internal leakage capacitances and Y-capacitors. The current values are proportional to the supply voltage and are specified in the table below. They are specified in the Table 13.

Table 13: Touch current

Characteristics		Class I	Unit
Maximum touch current	Permissible according to IEC/EN 62368-1	5.0	mA
	Typical value at 264 V, 60 Hz	3.5	

Protective Lacquer

All boards of the converters are coated with a protective lacquer. The rack including the back plane is designed with higher creepage distances and clearances, but is not protected by lacquer.

Asia-Pacific
+86 755 298 85888
EMEA
+353 61 531 820
North America
+1 866 513 2839
powersupport@belf.com
belfuse.com

© 2025 Bel Fuse Inc.

Isolation and Safety Test

The electric strength test of the converters is performed in the factory as routine test in accordance with EN 62911 and IEC/EN 62368-1.

The racks are tested without converters, but with all relays and signalling circuits.

Table 14 is valid for the racks populated with converters.

Table 14: Isolation (including converters which are separately tested)

Characteristics		Input to case and output(s)	Output(s) to case and input	Output 1 to output 2	Alarm signals to everything	Unit
Electric strength test	Factory test 1 to 6 s	2.8 [1]	4.3	0.18	4.3	kVDC
	AC test voltage equivalent to factory test	2.0	3.0	0.12	3.0	kVAC
Insulation resistance at 500 VDC		>300	>100 [2]	--	--	MΩ
Creepage distances	converters	≥3.2 [3]	≥4.5	--	--	mm
	racks	≥6.4	≥6.4	--	≥6.4	

[1] Subassemblies (of converters and rack) connecting input to output (e.g. transformers, opto couplers, relays, etc.) are pre-tested with 5.6 kVDC or 4 kVAC.

[2] Tested with 150 VDC

[3] Input to outputs: 6.4 mm

Accessories

Blank Panel / Filler HZZ02017G



Fig. 15
Blank Panel HZZ02017G

NUCLEAR AND MEDICAL APPLICATIONS - These products are not designed or intended for use as critical components in life support systems, equipment used in hazardous environments, or nuclear control systems.

TECHNICAL REVISIONS - The appearance of products, including safety agency certifications pictured on labels, may change depending on the date manufactured. Specifications are subject to change without notice.

POWER | PROTECT | CONNECT

Asia-Pacific +86 755 298 85888
EMEA +353 61 531 820
North America +1 866 513 2839

powersupport@belf.com
belfuse.com