Eaton 7.2OEFMA100

Oil fuse-link, medium voltage, 100 A, AC 7.2 kV, BS2692 F01, 254 x 63.5 mm, back-up, BS, IEC, ESI, with striker

PRODUCT NAME	Eaton Bussmann series medium voltage oil fuse
CATALOG NUMBER	7.2OEFMA100
UPC	051712837354
PRODUCT LENGTH/DEPTH	254 mm
PRODUCT HEIGHT	63.5 mm
PRODUCT WIDTH	63.5 mm
PRODUCT WEIGHT	1900 g
COMPLIANCES	BS 2692-1 ESI 12-8
CERTIFICATIONS	IEC Rated IEC60282-1

Powering Business Worldwide

□□□□	
AMPERAGE RATING	100 A
FUSE INDICATOR	with striker
FUSE SIZE	254 x 63.5 mm
BREAKING CAPACITY	31.5 kA
INSTALLATION TECHNIQUE	Oil
PERFORMANCE CAT ACCORDING TO IEC 60282-1	Back-up
PRODUCT APPLICATION	Primary side transformer protection
RATED FREQUENCY - MAX	60 Hz
RATED FREQUENCY - MIN	50 Hz
RELEASE CHARACTERISTIC	Other
STANDARD	British Standard
UTILIZATION CATEGORY	Other
VOLTAGE TYPE	AC
WITH STRIKER	Yes
FUSE DIAMETER	63.5 mm
JOULE INTEGRAL (I2T) - MAX OPERATING	9 x 104
JOULE INTEGRAL (I2T) - MIN PRE-ARCING	6.3 x 103
RESISTANCE	5.59
CLASS	Class back-up
BARRELS	1
CONSTRUCTION TYPE	F01/BS 2692
FUSE SHAPE	Cylindrical
INTERRUPT RATING	45 kAIC
CONSTRUCTION SIZE	63.5 x 254 mm
VOLTAGE RATING	7.2 kV
TYPE	fuse
APPLICATION	protection of primary side transformer, and oil-filled fuse switch combination unit
FUSE TYPE	OEFM

□□

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□