Eaton GSA600

Fuse-link, high speed, 600 A, AC 240 V, DC 200 V, BS88, 35 x 78 x 85 mm, aR, BS

PRODUCT NAME	Eaton Bussmann series high speed british standard fuse
CATALOG NUMBER	GSA600
UPC	051712485333
PRODUCT LENGTH/DEPTH	85 mm
PRODUCT HEIGHT	77.6 mm
PRODUCT WIDTH	34.6 mm
PRODUCT WEIGHT	0.453592 g
CERTIFICATIONS	BS88

Powering Business Worldwide

□□□□

AMPERAGE RATING	600 A
BREAKING CAPACITY	100 kA
FUSE INDICATOR	None
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC/DC
RATED SWITCHING CAPACITY	100 kA
RATED VOLTAGE AC	240 V
RATED VOLTAGE DC	200 V
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	60.3 mm
MOUNTING DIMENSION	M10
CURRENT TYPE	AC/DC
CLASS	Class aR
FUSE SHAPE	Offset dual barrel bolted tags
COLOR	None
CONSTRUCTION SIZE	Other
VOLTAGE RATING	240 V
TYPE	Fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
FUSE TYPE	GSA
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

□□

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□