

FEATURES

- High efficiency, low output ripple and noise
- Wide voltage input 2:1
- No external element required
- Continuous short circuit protection and self-recovery
- Operating temperature range: -40 ~ +85
- Isolation Voltage: 1500VDC
- Metal shield package
- High Reliability (MTTF ≥ 100 ten thousand hours)
- International standard pin mode
- 100% full load aging



RoHS
Isolate/Stabilivolt
Wide voltage input

PRODUCT MODEL LIST

Order Code	Normal Input Voltage (V)			Normal Output Voltage			Efficiency (%)		Capacitive Load [Max] (uF)
	Normal	Range	Max	Voltage (V)	Current (mA)		Min	Typ	
					Min	Max			
J10M12D03B	12	9~18	20	±3.3	0	±1515	78	80	3300
J10M12D05B				±5	0	±1000	80	82	2200
J10M12D09B				±9	0	±556	83	85	1000
J10M12D12B				±12	0	±417	84	86	680
J10M12D15B				±15	0	±333	85	87	470
J10M12D24B				±24	0	±208	85	87	220
J10M12S03B				3.3	0	3030	78	80	4700
J10M12S05B				5	0	2000	79	81	3300
J10M12S09B				9	0	1111	82	84	2200
J10M12S12B				12	0	833	84	86	1000
J10M12S15B				15	0	667	85	87	680
J10M12S24B				24	0	417	85	87	470
J10M24D03B				24	18~36	40	±3.3	0	±1515
J10M24D05B	±5	0	±1000				81	83	2200
J10M24D09B	±9	0	±556				83	85	1000
J10M24D12B	±12	0	±417				84	86	680
J10M24D15B	±15	0	±333				85	87	470
J10M24D24B	±24	0	±208				85	87	220
J10M24S03B	3.3	0	3030				78	80	4700
J10M24S05B	5	0	2000				81	83	3300
J10M24S09B	9	0	1111				84	86	2200
J10M24S12B	12	0	833				85	87	1000
J10M24S15B	15	0	667				86	88	680
J10M24S24B	24	0	417				86	88	470
J10M48D03B	48	36~72	75				±3.3	0	±1515
J10M48D05B				±5	0	±1000	81	83	2200
J10M48D09B				±9	0	±556	84	86	1000
J10M48D12B				±12	0	±417	85	87	680
J10M48D15B				±15	0	±333	86	88	470
J10M48D24B				±24	0	±208	85	87	220
J10M48S03B				3.3	0	3030	78	80	4700
J10M48S05B				5	0	2000	82	84	3300
J10M48S09B				9	0	1111	84	86	2200

All Specifications Subject To Change Without Notice

PRODUCT MODEL LIST

Order Code	Nominal Input Voltage (V)			Nominal Input Voltage			Efficiency (%)		Capacitive Load [Max] (uF)
	Nominal	Range	Max	Voltage (V)	Current (mA)		Min	Typ	
					Min	Max			
J10M48S12B	48	36~72	75	12	0	833	85	87	1000
J10M48S15B				15	0	667	86	88	680
J10M48S24B				24	0	417	86	88	470

Ps : *The positive and negative output capacitive loads are the same.

OUTPUT CHARACTERISTICS

Parameter	Conditions	Min.	Typ.	Max.	Units
Output Power		0		10	W
Output Positive Voltage Accuracy			±1	±2	%
Output Negative Voltage Accuracy			±2	±3	
Line Voltage Regulation	Full load, input voltage change from low to high		±0.2	±0.5	
Load Regulation	Load varies from 5% to 100% at nominal input		±0.5	±1	
Temps Drift Coefficient	Rated load			±0.03	%/
Ripple & Noise	At 20MHz bandwidth		50	100	mVp-p
Switching Frequency	Rated input voltage		320	350	KHz
Output Short Circuit Protection	Sustainable and automatic restoration				
Input Filter	π-type filtering				
Hot Plug	Nonsupport				

INPUT CHARACTERISTICS

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Undervoltage Protection	Input 12VDC	6.6	7.3		VDC
	Input 24VDC	13.5	14.8		
	Input 48VDC	27	30		
Starting Voltage	Input 12VDC		8.2	9	
	Input 24VDC		16.2	18	
	Input 48VDC		33	36	
Impulse Voltage (1sec. max)	Input 12VDC	-0.7		25	
	Input 24VDC			50	
	Input 48VDC			100	
No-load Current	Input 12VDC		10	15	mA
	Input 24VDC		5	10	
	Input 48VDC		3	5	

EMC CHARACTERISTICS


EMI	CE	CISPR32/EN55032 CLASS B (see EMI recommended circuit)		
	RE	CISPR32/EN55032 CLASS B (see EMI recommended circuit)		
EMS	ESD	IEC/EN61000 - 4 - 2 CONTACT ± 4KV		perf. Criteria B
	RS	IEC/EN61000 - 4 - 3 10V/M		perf. Criteria A
	EFT	IEC/EN61000 - 4 - 4 ± 2KV (see EMS recommended circuit)		perf. Criteria B
	Surge	IEC/EN61000 - 4 - 5 LINE TO LINE ± 2KV (see EMS recommended circuit)		perf. Criteria B
	CS	IEC/EN61000 - 4 - 6 3 VR.M.S		perf. Criteria A
	Voltage sag, drop and short - time interrupt immunity	IEC/EN61000 - 4 - 29 0% , 70%		perf. Criteria B

All Specifications Subject To Change Without Notice


Insulation Characteristic					
Parameter	Conditions	Min.	Typ.	Max.	Units
Insulation Resistance	Input- output, 500VDC	1000			M
Insulation Voltage	Input- output, test time 1 minute, leakage current less than 1 mA	1500			VDC
	Input、 output-shell, test time 1 minute, leakage current less than 1 mA	1000			

General Characteristic					
Parameter	Conditions	Min.	Typ.	Max.	Units
Storage Humidity		5		95	%
Operating Temps		-40		85	
Storage Temps		-55		125	
Operating Case Temps			20	30	
Pin Welding Temps	Welding joint 1.5mm from case,10 seconds operation			300	
MTTF	MIL - HDBK - 217@25	100			10000 hours
Weight			12		g
Cooling	Free air convection				
Case Material	White metal shell				

Temps Curve



Shape & Pin Dimensions




Pin	Single	Double
2,3	GND	GND
9	NC	0V
11	NC	-Vo
14	+Vo	+Vo
16	0V	0V
22,23	Vin	Vin


ps:
 NC: can't connect to any external circuit
 Terminal Spec.: 0.6
 Unit: MM
 Terminal section tolerance: ± 0.10 [± 0.004]
 Unmarked tolerance: ± 0.50 [± 0.020]

PCB

[0.1inch]2.54mm square grid




Package Dimensions




All Specifications Subject To Change Without Notice

EMC Recommended Circuit

3.3/5VDC OUTPUT



OTHER OUTPUT




Notes : The first red frame is for EMS test, the second red frame is for EMI test. Select as needed.

INPUT	FUSE	C0/C4	C1/C2	C3	LDM1	LCM1	CY1/CY2
12VDC	See remarks	470uF/35V	1uF/50V	See remarks	10uH	1.4~1.7mH	1nF/2kV
24VDC		330uF/50V					
48VDC		330uF/100V	1uF/100V				

Notes :
 FUSE: selection is according to customer's actual input current
 C3: refer to the output parameters in the application circuit.

Basic Application Circuit



Options of C1、C2:


Input Voltage	External Capacitance C1	Single Output Voltage	External Capacitance C2	Double Output Voltage	External Capacitance C2
--	--	5VDC	10uF/16V	± 5VDC	10uF/16V
12VDC	100uF/25V	9VDC	10uF/16V	± 9VDC	10uF/16V
24VDC	100uF/50V	12/15VDC	10uF/25V	± 12/± 15VDC	10uF/25V
48VDC	47uF/100V	24VDC	10uF/50V	± 24VDC	10uF/50V

Note


Avoid Excessive Output External Capacitance: The capacity value of the output external capacitor C2 should not be too large, otherwise it is easy to cause overcurrent or bad startup when the module is started. The specific value should be selected according to the external capacitor table.

The input of this series does not support parallel use of hot plug and output.

For situations requiring high ripple noise, external LC filter circuit should be connected, and the resonant frequency of LC filter should be far less than the switching frequency of DC/DC module to prevent mutual interference, resulting in output ripple increase or module damage, as shown in the figure:



Naming Logic Of Constant Voltage Products



All Specifications Subject To Change Without Notice