

芯伯乐®
X I N B O L E

Product Specification

XBLW SN74LVC1G126

Single Bus Buffer Gate With 3-State Output

WEB | www.xinboleic.com




Description

The 74LVC1G126 is a single buffer/line driver with 3-state output. Inputs can be driven from either 3.3 V or 5 V devices. This feature allows the use of these devices as translators in mixed 3.3 V and 5 V environments. Schmitt-trigger action at all inputs makes the circuit tolerant of slower input rise and fall times. This device is fully specified for partial power down applications using I OFF. The I OFF circuitry disables the output, preventing the potentially damaging backflow current through the device when it is powered down.

Features

- ±24 mA output drive (VCC = 3.0 V)
- CMOS low power consumption
- Direct interface with TTL levels
- Latch-up performance exceeds 250 mA
- Overvoltage tolerant inputs to 5.5 V
- Wide supply voltage range from 1.65 V to 5.5 V
- Spec'ed from -40 °C to +105 °C
- Packaging information: SOT-23-5/SOT-353



Applications

- SSDs: Internal or External
- Power Line Communication Modems
- Motor Controls: High-Voltage
- Military: Radars and Sonars
- High-Speed Data Acquisition and Generation
- Cable Modem Termination Systems
- Video Communication Systems
- Video Broadcasting: IP-Based Multi-Format Transcoders
- Video Broadcasting and Infrastructure: Scalable Platforms



Ordering Information

| Product Model | Package Type | Marking | Packing | Packing Qty |
|-----------------------|--------------|---------|---------|--------------|
| XBLW SN74LVC1G126T235 | SOT-23-5 | AGXX | Tape | 3000Pcs/Reel |
| XBLW SN74LVC1G126T353 | SOT-353 | AGXX | Tape | 3000Pcs/Reel |

Block Diagram




Figure 1. Logic symbol



Figure 2. IEC logic symbol





Figure 3. Logic diagram

Pin Configurations



Pin Description

| Pin No. | Pin Name | Description |
|---------|-----------------|---------------------|
| 1 | OE | output enable input |
| 2 | A | data input |
| 3 | GND | ground (0V) |
| 4 | Y | data output |
| 5 | V _{CC} | supply voltage |

Function Table

| Input | | Output |
|-------|---|--------|
| OE | A | Y |
| H | L | L |
| H | H | H |
| L | X | Z |

Note: H=HIGH voltage level; L=LOW voltage level; X=don't care; Z=high-impedance OFF-state.

Electrical Parameter

Absolute Maximum Ratings

(Voltages are referenced to GND(ground=0V), unless otherwise specified.)

| Parameter | Symbol | Conditions | Min. | Max. | Unit |
|-------------------------|-----------|------------------------------|------|--------------|------|
| supply voltage | V_{CC} | - | -0.5 | 6.5 | V |
| output voltage | V_O | Active mode | -0.5 | $V_{CC}+0.5$ | V |
| | | Power-down mode | -0.5 | 6.5 | V |
| input voltage | V_i | - | -0.5 | 6.5 | V |
| input clamping current | I_{IK} | $V_i < 0V$ | -50 | - | mA |
| Output clamping current | I_{OK} | $V_o > V_{CC}$ or $V_o < 0V$ | - | ± 50 | mA |
| output current | I_O | $V_o=0V$ to V_{CC} | - | ± 50 | mA |
| supply current | I_{CC} | - | - | 100 | mA |
| ground current | I_{GND} | - | -100 | - | mA |
| total power dissipation | P_{tot} | - | - | 250 | mW |
| storage temperature | T_{stg} | - | -65 | 150 | °C |
| Soldering temperature | T_L | 10s | - | 250 | °C |

Recommended Operating Conditions

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Unit |
|-------------------------------------|---------------------|------------------------------|------|------|----------|------|
| supply voltage | V_{CC} | - | 1.65 | - | 5.5 | V |
| input voltage | V_i | - | 0 | - | 5.5 | V |
| output voltage | V_O | Active mode | 0 | - | V_{CC} | V |
| | | Power-down mode; $V_{CC}=0V$ | 0 | - | 5.5 | V |
| ambient temperature | T_{amb} | - | -40 | - | 105 | °C |
| input transition rise and fall rate | $\Delta t/\Delta V$ | $V_{CC}=1.65V$ to $2.7V$ | - | - | 20 | ns/V |
| | | $V_{CC}=2.7V$ to $5.5V$ | - | - | 10 | ns/V |

ESD Ratings

| Parameter | Definition | Value | Unit |
|-------------|---|------------|------|
| $V_{(ESD)}$ | Human body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins (1) | ± 2000 | V |
| | Charged device model (CDM), per JEDEC specification JESD22-C101, all pins (2) | ± 1000 | |

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

Electrical Characteristics

DC Characteristics 1

(Tamb=-40°C to +85°C, voltages are referenced to GND (ground=0V), unless otherwise specified.)

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Unit | |
|---------------------------|------------------|--|---|----------------------|----------------------|------|---|
| HIGH-level input voltage | V _{IH} | V _{CC} =1.65V to 1.95V | 0.65xV _{CC} | - | - | V | |
| | | V _{CC} =2.3V to 2.7V | 1.7 | - | - | V | |
| | | V _{CC} =2.7V to 3.6V | 2.0 | - | - | V | |
| | | V _{CC} =4.5V to 5.5V | 0.7xV _{CC} | - | - | V | |
| LOW-level input voltage | V _{IL} | V _{CC} =1.65V to 1.95V | - | - | 0.35xV _{CC} | V | |
| | | V _{CC} =2.3V to 2.7V | - | - | 0.7 | V | |
| | | V _{CC} =2.7V to 3.6V | - | - | 0.8 | V | |
| | | V _{CC} =4.5V to 5.5V | - | - | 0.3xV _{CC} | V | |
| HIGH-level output voltage | V _{OH} | V _I = V _{IH} or V _{IL} | I _O =-100uA; V _{CC} =1.65V to 5.5V | V _{CC} -0.1 | - | - | V |
| | | | I _O =-4mA; V _{CC} =1.65V | 1.2 | - | - | V |
| | | | I _O =-8mA; V _{CC} =2.3V | 1.9 | - | - | V |
| | | | I _O =-12mA; V _{CC} =2.7V | 2.2 | - | - | V |
| | | | I _O =-24mA; V _{CC} =3.0V | 2.3 | - | - | V |
| | | | I _O =-32mA; V _{CC} =4.5V | 3.8 | - | - | V |
| LOW-level output voltage | V _{OL} | V _I = V _{IH} or V _{IL} | I _O =100uA; V _{CC} =1.65V to 5.5V | - | - | 0.10 | V |
| | | | I _O =4mA; V _{CC} =1.65V | - | - | 0.45 | V |
| | | | I _O =8mA; V _{CC} =2.3V | - | - | 0.30 | V |
| | | | I _O =12mA; V _{CC} =2.7V | - | - | 0.40 | V |
| | | | I _O =24mA; V _{CC} =3.0V | - | - | 0.55 | V |
| | | | I _O =32mA; V _{CC} =4.5V | - | - | 0.55 | V |
| input leakage current | I _i | V _I =5.5V or GND; V _{CC} =0V to 5.5V | - | - | ±1 | uA | |
| OFF-state output current | I _{OZ} | V _I =V _{IH} or V _{IL} ; V _O =5.5V or GND; V _{CC} =3.6V | - | - | ±2 | uA | |
| power-off leakage current | I _{OFF} | V _I or V _O =5.5V; V _{CC} =0V | - | - | ±2 | uA | |
| supply current | I _{CC} | V _I =5.5V or GND; I _O =0A; V _{CC} =1.65V to 5.5V | - | - | 4 | uA | |
| additional supply current | ΔI _{CC} | per pin; V _i =V _{CC} -0.6V; I _O =0A; V _{CC} =2.3V to 5.5V | - | 5 | 500 | uA | |
| input capacitance | C _i | - | - | 5 | - | pF | |

Note: All typical values are measured at V_{CC}=3.3V and Tamb=25°C.

DC Characteristics 2

(Tamb=-40°C to +105°C, voltages are referenced to GND (ground=0V), unless otherwise specified.)

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Unit | |
|---------------------------|------------------|--|---|----------------------|----------------------|------|---|
| HIGH-level input voltage | V _{IH} | V _{CC} =1.65V to 1.95V | 0.65xV _{CC} | - | - | V | |
| | | V _{CC} =2.3V to 2.7V | 1.7 | - | - | V | |
| | | V _{CC} =2.7V to 3.6V | 2.0 | - | - | V | |
| | | V _{CC} =4.5V to 5.5V | 0.7xV _{CC} | - | - | V | |
| LOW-level input voltage | V _{IL} | V _{CC} =1.65V to 1.95V | - | - | 0.35xV _{CC} | V | |
| | | V _{CC} =2.3V to 2.7V | - | - | 0.7 | V | |
| | | V _{CC} =2.7V to 3.6V | - | - | 0.8 | V | |
| | | V _{CC} =4.5V to 5.5V | - | - | 0.3xV _{CC} | V | |
| HIGH-level output voltage | V _{OH} | V _I = V _{IH} or V _{IL} | I _O =-100uA; V _{CC} =1.65V to 5.5V | V _{CC} -0.1 | - | - | V |
| | | | I _O =-4mA; V _{CC} =1.65V | 0.95 | - | - | V |
| | | | I _O =-8mA; V _{CC} =2.3V | 1.7 | - | - | V |
| | | | I _O =-12mA; V _{CC} =2.7V | 1.9 | - | - | V |
| | | | I _O =-24mA; V _{CC} =3.0V | 2.0 | - | - | V |
| | | | I _O =-32mA; V _{CC} =4.5V | 3.4 | - | - | V |
| LOW-level output voltage | V _{OL} | V _I = V _{IH} or V _{IL} | I _O =100uA; V _{CC} =1.65V to 5.5V | - | - | 0.10 | V |
| | | | I _O =4mA; V _{CC} =1.65V | - | - | 0.70 | V |
| | | | I _O =8mA; V _{CC} =2.3V | - | - | 0.45 | V |
| | | | I _O =12mA; V _{CC} =2.7V | - | - | 0.60 | V |
| | | | I _O =24mA; V _{CC} =3.0V | - | - | 0.80 | V |
| | | | I _O =32mA; V _{CC} =4.5V | - | - | 0.80 | V |
| input leakage current | I _i | V _I =5.5V or GND; V _{CC} =0V to 5.5V | - | - | ±1 | uA | |
| OFF-state output current | I _{OZ} | V _I =V _{IH} or V _{IL} ; V _O =5.5V or GND; V _{CC} =3.6V | - | - | ±2 | uA | |
| power-off leakage current | I _{OFF} | V _I or V _O =5.5V; V _{CC} =0V | - | - | ±2 | uA | |
| supply current | I _{CC} | V _I =5.5V or GND; I _O =0A; V _{CC} =1.65V to 5.5V | - | - | 4 | uA | |
| additional supply current | ΔI _{CC} | per pin; V _I =V _{CC} -0.6V; I _O =0A; V _{CC} =2.3V to 5.5V | - | - | 500 | uA | |

Note: All typical values are measured at V_{CC}=3.3V and Tamb=25°C.

AC Characteristics 1

 ($T_{amb}=-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

| Parameter | Symbol | Conditions | Min. | Typ. ^[1] | Max. | Unit | |
|--------------------------|--------------------|--------------|---------------------------------------|---------------------|------|------|----|
| A to Y propagation delay | t_{PLH}, t_{PHL} | see Figure 5 | $V_{CC}=1.65\text{V to }1.95\text{V}$ | - | 9.0 | 13.5 | ns |
| | | | $V_{CC}=2.3\text{V to }2.7\text{V}$ | - | 6.3 | 9.5 | ns |
| | | | $V_{CC}=2.7\text{V}$ | - | 6.9 | 10.4 | ns |
| | | | $V_{CC}=3.0\text{V to }3.6\text{V}$ | - | 6.0 | 9.0 | ns |
| | | | $V_{CC}=4.5\text{V to }5.5\text{V}$ | - | 5.1 | 7.7 | ns |
| OE to Y enable time | t_{PZH}, t_{PZL} | see Figure 6 | $V_{CC}=1.65\text{V to }1.95\text{V}$ | - | 9.6 | 14.4 | ns |
| | | | $V_{CC}=2.3\text{V to }2.7\text{V}$ | - | 6.6 | 9.9 | ns |
| | | | $V_{CC}=2.7\text{V}$ | - | 7.2 | 10.8 | ns |
| | | | $V_{CC}=3.0\text{V to }3.6\text{V}$ | - | 6.3 | 9.5 | ns |
| | | | $V_{CC}=4.5\text{V to }5.5\text{V}$ | - | 4.8 | 7.2 | ns |
| OE to Y disable time | t_{PLZ}, t_{PHZ} | see Figure 6 | $V_{CC}=1.65\text{V to }1.95\text{V}$ | - | 12.9 | 19.4 | ns |
| | | | $V_{CC}=2.3\text{V to }2.7\text{V}$ | - | 8.1 | 12.2 | ns |
| | | | $V_{CC}=2.7\text{V}$ | - | 10.2 | 15.3 | ns |
| | | | $V_{CC}=3.0\text{V to }3.6\text{V}$ | - | 9.0 | 13.5 | ns |
| | | | $V_{CC}=4.5\text{V to }5.5\text{V}$ | - | 6.6 | 9.9 | ns |

Note:

 [1] Typical values are measured at $T_{amb}=25^{\circ}\text{C}$ and $V_{CC}=1.8\text{V}, 2.5\text{V}, 2.7\text{V}, 3.3\text{V}$ and 5.0V respectively.

AC Characteristics 2

 ($T_{amb}=-40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Unit | |
|--------------------------|--------------------|--------------|---------------------------------------|------|------|------|----|
| A to Y propagation delay | t_{PLH}, t_{PHL} | see Figure 5 | $V_{CC}=1.65\text{V to }1.95\text{V}$ | - | - | 17.7 | ns |
| | | | $V_{CC}=2.3\text{V to }2.7\text{V}$ | - | - | 12.0 | ns |
| | | | $V_{CC}=2.7\text{V}$ | - | - | 13.2 | ns |
| | | | $V_{CC}=3.0\text{V to }3.6\text{V}$ | - | - | 12.0 | ns |
| | | | $V_{CC}=4.5\text{V to }5.5\text{V}$ | - | - | 10.5 | ns |
| OE to Y enable time | t_{PZH}, t_{PZL} | see Figure 6 | $V_{CC}=1.65\text{V to }1.95\text{V}$ | - | - | 18.4 | ns |
| | | | $V_{CC}=2.3\text{V to }2.7\text{V}$ | - | - | 12.8 | ns |
| | | | $V_{CC}=2.7\text{V}$ | - | - | 13.9 | ns |
| | | | $V_{CC}=3.0\text{V to }3.6\text{V}$ | - | - | 12.5 | ns |
| | | | $V_{CC}=4.5\text{V to }5.5\text{V}$ | - | - | 9.4 | ns |
| OE to Y disable time | t_{PLZ}, t_{PHZ} | see Figure 6 | $V_{CC}=1.65\text{V to }1.95\text{V}$ | - | - | 25.2 | ns |
| | | | $V_{CC}=2.3\text{V to }2.7\text{V}$ | - | - | 15.5 | ns |
| | | | $V_{CC}=2.7\text{V}$ | - | - | 19.5 | ns |
| | | | $V_{CC}=3.0\text{V to }3.6\text{V}$ | - | - | 17.2 | ns |
| | | | $V_{CC}=4.5\text{V to }5.5\text{V}$ | - | - | 13.0 | ns |

Testing Circuit

AC Testing Circuit




Figure 4. Test circuit for measuring switching times

Definitions for test circuit:

R_L =Load resistance.

C_L =Load capacitance including jig and probe capacitance.

R_T =Termination resistance; should be equal to the output impedance Z_o of the pulse generator.

V_{EXT} =External voltage for measuring switching times.

AC Testing Waveforms




Figure 5. The input A to output Y propagation delay times




Figure 6. 3-state enable and disable times

Measurement Points

| Supply voltage | Input | Output | | |
|-----------------|-----------------------|-----------------------|------------------------|------------------------|
| V _{CC} | V _M | V _M | V _X | V _Y |
| 1.65V to 1.95 V | 0.5 × V _{CC} | 0.5 × V _{CC} | V _{OL} +0.15V | V _{OH} -0.15V |
| 2.3V to 2.7V | 0.5 × V _{CC} | 0.5 × V _{CC} | V _{OL} +0.15V | V _{OH} -0.15V |
| 2.7V | 1.5V | 1.5V | V _{OL} +0.3V | V _{OH} -0.3V |
| 3.0V to 3.6V | 1.5V | 1.5V | V _{OL} +0.3V | V _{OH} -0.3V |
| 4.5V to 5.5V | 0.5 × V _{CC} | 0.5 × V _{CC} | V _{OL} +0.3V | V _{OH} -0.3V |


Test Data

| Supply voltage | Input | | Load | | V _{EXT} | | |
|-----------------|-----------------|---------------------------------|----------------|----------------|-------------------------------------|-------------------------------------|-------------------------------------|
| V _{CC} | V _I | T _r , t _f | C _L | R _L | t _{PLH} , t _{PHL} | t _{PZH} , t _{PHZ} | t _{PZL} , t _{PLZ} |
| 1.65V to 1.95 V | V _{CC} | ≤ 2.0ns | 30pF | 1kQ | open | GND | 2 × V _{CC} |
| 2.3V to 2.7V | V _{CC} | ≤ 2.0ns | 30pF | 500Q | open | GND | 2 × V _{CC} |
| 2.7V | 2.7V | ≤ 2.5ns | 50pF | 500Q | open | GND | 6V |
| 3.0V to 3.6V | 2.7V | ≤ 2.5ns | 50pF | 500Q | open | GND | 6V |
| 4.5V to 5.5V | V _{CC} | ≤ 2.5ns | 50pF | 500Q | open | GND | 2 × V _{CC} |

Package Information


- SOT23-5

| SIZE SYMBOL | Dimensions In Millimeters | | SIZE SYMBOL | Dimensions In Inches | |
|----------------|---------------------------|----------|----------------|----------------------|----------|
| | MIN (mm) | MAX (mm) | | MIN (in) | MAX (in) |
| A | 1.050 | 1.250 | A | 0.041 | 0.049 |
| A1 | 0.000 | 0.100 | A1 | 0.000 | 0.004 |
| A2 | 1.050 | 1.150 | A2 | 0.041 | 0.045 |
| b | 0.300 | 0.500 | b | 0.012 | 0.020 |
| c | 0.100 | 0.200 | c | 0.004 | 0.008 |
| D | 2.820 | 3.020 | D | 0.111 | 0.119 |
| E | 1.500 | 1.700 | E | 0.059 | 0.067 |
| E1 | 2.650 | 2.950 | E1 | 0.104 | 0.116 |
| e | 0.95 (BSC) | | e | 0.037 (BSC) | |
| e1 | 1.800 | 2.000 | e1 | 0.071 | 0.079 |
| L | 0.300 | 0.600 | L | 0.012 | 0.024 |
| θ | 0° | 8° | θ | 0° | 8° |



• SOT-353

| Size Symbol | Dimensions In Millimeters | | Size Symbol | Dimensions In Inches | |
|----------------|---------------------------|----------|----------------|----------------------|----------|
| | Min (mm) | Max (mm) | | Min (in) | Max (in) |
| A | 0.900 | 1.100 | A | 0.035 | 0.043 |
| A1 | 0.000 | 0.100 | A1 | 0.000 | 0.004 |
| A2 | 0.900 | 1.000 | A2 | 0.035 | 0.039 |
| b | 0.150 | 0.350 | b | 0.006 | 0.014 |
| c | 0.080 | 0.150 | C | 0.003 | 0.006 |
| D | 2.000 | 2.200 | D | 0.079 | 0.087 |
| E | 1.150 | 1.350 | E | 0.045 | 0.053 |
| E1 | 2.150 | 2.450 | E1 | 0.085 | 0.096 |
| e | 0.650 (TYP) | | e | 0.026 (TYP) | |
| e1 | 1.200 | 1.400 | e1 | 0.047 | 0.055 |
| L | 0.525 (REF) | | L | 0.021 (REF) | |
| L1 | 0.260 | 0.460 | L1 | 0.010 | 0.018 |
| θ | 0° | 8° | θ | 0° | 8° |



Statement:

- XBLW reserves the right to modify the product manual without prior notice! Before placing an order, customers need to confirm whether the obtained information is the latest version and verify the completeness of the relevant information.
- Any semi-guide product is subject to failure or malfunction under specified conditions. It is the buyer's responsibility to comply with safety standards when using XBLW products for system design and whole machine manufacturing. And take the appropriate safety measures to avoid the potential in the risk of loss of personal injury or loss of property situation!
- XBLW products have not been licensed for life support, military, and aerospace applications, and therefore XBLW is not responsible for any consequences arising from the use of this product in these areas.
- If any or all XBLW products (including technical data, services) described or contained in this document are subject to any applicable local export control laws and regulations, they may not be exported without an export license from the relevant authorities in accordance with such laws.
- The specifications of any and all XBLW products described or contained in this document specify the performance, characteristics, and functionality of said products in their standalone state, but do not guarantee the performance, characteristics, and functionality of said products installed in Customer's products or equipment. In order to verify symptoms and conditions that cannot be evaluated in a standalone device, the Customer should ultimately evaluate and test the device installed in the Customer's product device.
- XBLW documentation is only allowed to be copied without any alteration of the content and with the relevant authorization. XBLW assumes no responsibility or liability for altered documents.
- XBLW is committed to becoming the preferred semiconductor brand for customers, and XBLW will strive to provide customers with better performance and better quality products.