Eaton FWJ-60A

Eaton Bussmann series FWJ high speed fuse, 700 Vac (UL), 690 Vac (IEC), 800 Vdc (5-50A), 60A, 25 kAIC (35-200A), 100 kAIC (250-2000A), 50 kAIC at 800 Vdc (35-200A, 450-600A), None, High speed fuse, Blade end X blade end, Stud

PRODUCT NAME	Eaton Bussmann series high speed cylindrical fuse
CATALOG NUMBER	FWJ-60A
UPC	051712796156
PRODUCT LENGTH/DEPTH	19 mm
PRODUCT HEIGHT	19 mm
PRODUCT WIDTH	127 mm
PRODUCT WEIGHT	120 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Recognized CSA Certified

Powering Business Worldwide

□□□□	
AMPERAGE RATING	600 A
BREAKING CAPACITY	25 kA
FUSE INDICATOR	Non Indicating
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC/DC
RATED SWITCHING CAPACITY	25 A
RATED VOLTAGE AC	1000 V
RATED VOLTAGE DC	800 V
MOUNTING DIMENSION	M8
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	106.91 mm
CURRENT TYPE	AC/DC
CLASS	Class aR
CLEARING (I2T)	5000 at 1000 V
WATT LOSSES	11 W
FUSE SHAPE	Cylindrical, center bolted tags
PRE ARC (I2T)	670
COLOR	None
INTERRUPT RATING	450-600A) 50 kAIC at 800 Vdc (35-200A 100 kAIC (250-2000A) 25 kAIC (35-200A)
CONNECTION	Blade end x blade end
CONSTRUCTION SIZE	Other
MOUNTING METHOD	Stud
PACKAGING TYPE	Standard
VOLTAGE RATING	1000 Vac, 800 Vdc
TYPE	High speed fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
FUSE TYPE	FWJ-A
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

□□

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□