Eaton 10D16Q

Fuse-link, low voltage, 10 A, AC 500 V, D1, 13.2 x 6 mm, gR, IEC, Fast acting

□□□□	
PRODUCT NAME	Eaton Bussmann series low voltage D fuse
CATALOG NUMBER	10D16Q
UPC	051712830379
PRODUCT LENGTH/DEPTH	50 mm
PRODUCT HEIGHT	13.2 mm
PRODUCT WIDTH	13.2 mm
PRODUCT WEIGHT	14.5 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	IEC 60269 EAC DIN EN 60269-3 (VDE 0636 Part 30) DIN EN 60269-1 (VDE 0636 Part 10) DIN VDE 0636-301

Powering Business Worldwide

□□□□	
AMPERAGE RATING	10 A
FUSE SIZE	DI
BREAKING CAPACITY	50 kA
CONSTRUCTION SIZE (FUSE INSERTS)	DI
RATED VOLTAGE AC	500 V
CLASS	Class gR
FUSE TYPE	D16Q - Fast acting
UTILIZATION CATEGORY	gR (general purpose semiconductor protection)
ACCESSORY/SPARE PART TYPE	10GD16 Red screw cap gauge piece
COLOR	Red
INTERRUPT RATING	50 kAIC
FUSE INDICATOR	Non-indicating
CONNECTION	Other
CONSTRUCTION	D1
CONSTRUCTION SIZE	DI
FUSE SHAPE	Bottle
RESPONSE TIME	Fast-acting
SUITABLE FOR	E16/DI Fuse base
MATERIAL	White ceramic body
MOUNTING METHOD	Holder
PACKAGING TYPE	Standard
RELEASE CHARACTERISTIC	Fast (F)
VOLTAGE RATING	500 V
TYPE	Fuse
SPECIAL FEATURES	Fast-acting
APPLICATION	For domestic and general industrial applications

□□	
DECLARATIONS OF CONFORMITY	eaton-low-voltage-d-fuse-declaration-of-conformity-uk251016en.pdf

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□