# Eaton GSGB25

Fuse-link, high speed, 25 A, AC 660 V, DC 400 V, BS88, 17 x 80 mm, aR, BS, Ultra fast

| | |
|---|---|
| **PRODUCT NAME** | Eaton Bussmann series high speed british standard fuse |
| **CATALOG NUMBER** | GSGB25 |
| **UPC** | 051712392266 |
| **PRODUCT LENGTH/DEPTH** | 80 mm |
| **PRODUCT HEIGHT** | 18 mm |
| **PRODUCT WIDTH** | 18 mm |
| **PRODUCT WEIGHT** | 33.35 g |
| **COMPLIANCES** | CE Marked |
| **CERTIFICATIONS** | UL Recognized |

Powering Business Worldwide

## □□□□

| | |
|---|---|
| **AMPERAGE RATING** | 25 A |
| **BREAKING CAPACITY** | 100 kA |
| **FUSE INDICATOR** | None |
| **INSULATED METAL GRIPPING LUGS (IMGL)** | No |
| **UTILIZATION CATEGORY** | aR (accompanied semiconductor protection) |
| **VOLTAGE TYPE** | AC/DC |
| **RATED SWITCHING CAPACITY** | 100 kA |
| **RATED VOLTAGE AC** | 660 V |
| **RATED VOLTAGE DC** | 400 V |
| **CENTER-TO-CENTER DISTANCE OF CONNECTIONS** | 61.8 mm |
| **MOUNTING DIMENSION** | M6 |
| **CURRENT TYPE** | AC/DC |
| **CLASS** | Class aR |
| **WATT LOSSES** | 8.3 W |
| **FUSE SHAPE** | Offset bolted tags |
| **COLOR** | None |
| **CONSTRUCTION SIZE** | Other |
| **PACKAGING TYPE** | Standard |
| **VOLTAGE RATING** | 660 V |
| **TYPE** | Fuse |
| **APPLICATION** | Semiconductor, DC Common bus, DC drives, power converters/rectifiers |
| **FUSE TYPE** | GSG |
| **FUSE SYSTEM (ACCORDING TO IEC 60269)** | Other |

## □□

| | |
|---|---|
| □□□□: | |
| □□□□: | |
| □□□: | |
| □□: | |

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□