

35-411-151-R ✓ ACTIVE

KISSLING | KISSLING Series 35

TE Internal #: K1143304

400 A Battery Disconnect Switch, 32 VDC, 1 Pole, Pointer Key Handle, 0 Auxillary Positions, Long Flange, Not Removable, Red Handle, KISSLING Series 35

[View on TE.com >](#)



Switches > Battery Disconnect Switches > Battery Disconnect, 400A, 1 Pole



Switch Main Contact Current Rating: **400 A**

Operating Voltage: **32 VDC**

Number of Poles: **1**

Operating Handle Type: **Pointer Key Handle**

Termination Thread Size: **M10**

[All Battery Disconnect, 400A, 1 Pole \(22\)](#)

Features

Product Type Features

Sealed Device	Yes
---------------	-----

Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
-----------------------------	---------------------------

Dimensions

Screw Hole Diameter	6.5 mm[.256 in]
---------------------	-----------------

Centerline Between Flange Screw Holes	100 mm[3.937 in]
---------------------------------------	------------------

Electrical Characteristics

Operating Voltage	32 VDC
-------------------	--------

Switch Main Contact Current Rating	400 A
------------------------------------	-------

Configuration Features

Number of Poles	1
-----------------	---

Number of Auxiliary Contacts	0
------------------------------	---

Switch Keying Option	Not Removable
----------------------	---------------

Mechanical Attachment

Operating Handle Type	Pointer Key Handle
-----------------------	--------------------



Termination Thread Size	M10
-------------------------	-----

Switch Mounting Option	Long Flange
------------------------	-------------

Body Features

Operating Handle Color	Red
------------------------	-----

Other

EU RoHS Compliance	Compliant with Exemptions
--------------------	---------------------------

EU ELV Compliance	Compliant with Exemptions
-------------------	---------------------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
------------------------------	---------------------------

EU ELV Directive 2000/53/EC	Compliant with Exemptions
-----------------------------	---------------------------

China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
---	--------------------------------------

EU REACH Regulation (EC) No. 1907/2006	<p>Current ECHA Candidate List: JUNE 2024 (241)</p> <p>Candidate List Declared Against: JAN 2021 (211)</p> <p>SVHC > Threshold:</p> <p>Pb (2% in Component part)</p> <p>Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.</p>
--	--

Halogen Content	Not Yet Reviewed for halogen content
-----------------	--------------------------------------

Solder Process Capability	Not reviewed for solder process capability
---------------------------	--

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-AL4-SBD354001
Battery Disconnect, 400A, 1 Pole

Also in the Series | KISSLING Series 35



Battery Disconnect Switches(164)



Rotary Switches(6)

Customers Also Bought



TE Part #CAT-C4962-B128
Circular DIN Backshells



TE Part #2423921-1
Conn G SNG 38999 S1,2,4 Shell 21 & 22



TE Part #8-1618406-3
EV202ASAND=Relay, DPST-NO 28V



TE Part #4-1617791-5
FCA-125-3604L=M83536/36-004L



TE Part #YDTS26W17-35PNV001
PLUG ASSY



TE Part #DT06-4S
PLG, 4P, GRY, N



TE Part #NB12034001
ATUM-9/3-0-SP



TE Part #1-1393315-1
V23132B2002B200=HCR



TE Part #1062-12-0166
SOC, SF, SIZE 12, 12-14, NI/SN



Documents

Product Drawings

[Battery Disconnect 35-411-151-R](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_35-411-151-R_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_35-411-151-R_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_35-411-151-R_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[KISSLING BATTERY DISCONNECTOR Series 35 / 400A](#)

English