Eaton 20NZ02

Eaton Bussmann series low voltage D0 fuse, Time-delay, 400V, 20A, 100 kAIC, Non Indicating, fuse, Class C gL/gG, Holder, Blue, Ceramic body

PRODUCT NAME	Eaton Bussmann series low voltage D0 fuse
CATALOG NUMBER	20NZ02
UPC	051712832489
PRODUCT LENGTH/DEPTH	36 mm
PRODUCT HEIGHT	15 mm
PRODUCT WIDTH	15 mm
PRODUCT WEIGHT	12.3 g
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	VDE IEC 60269 DIN EN 60269-3 (VDE 0636 Part 30) DIN EN 60269-1 (VDE 0636 Part 10) DIN VDE 0636-301

Powering Business Worldwide

□□□□	
AMPERAGE RATING	20 A
FUSE SIZE	D02
BREAKING CAPACITY	50 kA
RATED VOLTAGE AC	400 V
CLASS	Class C gL/gG
FUSE TYPE	NZ02 - Time delay
UTILIZATION CATEGORY	gL/gG (cable protection/equipment protection)
ACCESSORY/SPARE PART TYPE	20GN02 Blue screw cap gauge piece
COLOR	Blue
INTERRUPT RATING	50 kAIC
FUSE INDICATOR	Non-indicating
CONNECTION	Other
CONSTRUCTION	D02
CONSTRUCTION SIZE	D02
FUSE SHAPE	Bottle
RESPONSE TIME	Time-delay
SUITABLE FOR	E18 (D02) Fuse base FRN02C Single-pole fuse base FN02C Single-pole fuse base FRN02-D Single-pole fuse base FRN02-SD Single-pole fuse base TFRN02C Three-pole fuse base TFN02C Three-pole fuse base TFRN02-D Three-pole fuse base TFRN02-SD Three-pole fuse base
MATERIAL	White ceramic body
MOUNTING METHOD	Holder
QUANTITY	10
VOLTAGE RATING	400 V
TYPE	fuse
SPECIAL FEATURES	Time-delay
APPLICATION	For domestic and general industrial applications

□□	
DECLARATIONS OF CONFORMITY	eaton-low-voltage-d-fuse-declaration-of-conformity-uk251016en.pdf

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□