



钲地半导体  
Tudi Semiconductor

## Product Specification

TUDI-ADM232

Enhanced RS-232 Line Drivers/Receivers

网址 [www.sztdbdt.com](http://www.sztdbdt.com) Q

用芯智造 · 卓越品质

**semiconductor device  
manufacturer**

- Design
- research and development
- production
- and sales





## Features

- 150Kbps Transmission Rate
- Small (0.1 F) Charge Pump Capacitors
- Single 5 V Power Supply
- Meets All EIA-232-E and V.28 Specifications
- Two Drivers and Two Receivers
- On-Board DC-DC Converters
- 7 V Output Swing with 5 V Supply

## Description

The ADM232A is a high-speed RS-232 line driver/receiver series that offers data rates up to 10kbps. These devices are powered by a single 5V supply and the efficient on-chip charge pump uses an external capacitor (0.1  $\mu$ F) to the RS-232 bipolar levels. Each device provides two RS-232 drivers and two RS232 receivers. The ADM232A is available DIP16 SOP16 and SMD16 packages.



Typical Operating Circuit



## Pin description

| Pin No | Symbol | Pin name                                                           |
|--------|--------|--------------------------------------------------------------------|
| 01     | C1+    | Output of external capacitance of positive voltage multiplier unit |
| 02     | V+     | Output of positive voltage of multiplier unit                      |
| 03     | C1-    | Output of external capacitance of positive voltage multiplier unit |
| 04     | C2+    | Output of external capacitance of negative voltage multiplier unit |
| 05     | C2-    | Output of external capacitance of negative voltage multiplier unit |
| 06     | V-     | Output of negative voltage of multiplier unit                      |
| 07     | T2oUT  | Output of transmitter data(levels RS-232)                          |
| 08     | R2IN   | Input of receiver data(levels RS-232)                              |
| 09     | R2oUT  | Output of receiver data(levels TTL/KMOS)                           |
| 10     | T2IN   | Input of transmitter data(levels TTL/KMOS)                         |
| 11     | T1n    | Input of transmitter data(levels TTL/KMOS)                         |
| 12     | R1oUT  | Output of receiver data(levels TTL/KMOS)                           |
| 13     | R1n    | Input of receiver data(levels RS-232)                              |
| 14     | T1oUT  | Output of transmitter data(levels RS-232)                          |
| 15     | GND    | Common output                                                      |
| 16     | Vcc    | Supply output of voltage source                                    |



### Recommended Operating Conditions

| Symbol | Parameter                                | Rate |     | Unit |
|--------|------------------------------------------|------|-----|------|
|        |                                          | min  | max |      |
| Vcc    | Supply voltage                           | 4.5  | 5.5 | V    |
| V+     | Transmitter output high voltage          | 5.0  | -   |      |
| V-     | Transmitter output low voltage           | -5.0 | -   |      |
| VTIN   | Transmitter input voltage                | 0    | Vcc |      |
| VRIN   | Receiver input voltage                   | -30  | 30  |      |
| Isc    | Transmitter short circuit output current | -    | ±60 | mA   |
| Ta     | Ambient temperature                      | -40  | 85  | C    |

### Maximum conditions

| Symbol | Parameter                                   | Rate    |              | Unit |
|--------|---------------------------------------------|---------|--------------|------|
|        |                                             | min     | max          |      |
| Vcc    | Supply voltage                              | -0.3    | 6.0          | V    |
| V+     | Transmitter high output voltage             | Vcc-0.3 | 14           |      |
| V-     | Transmitter low output voltage              | -0.3    | -14          |      |
| VTIN   | Transmitter input voltage                   | -0.3    | V++0.3       |      |
| VRIN   | Receiver input voltage                      | -30     | 30           |      |
| Pp     | Dissipated powerDIP-package                 | -       |              | mW   |
| Isc    | Output current of transmitter short circuit | -       | Continuously | mA   |
| Ta     | Ambient temperature                         | -60     | 150          | C    |



| Receiver electrical parameters    |                                   |                             |      |       |               |       |         |
|-----------------------------------|-----------------------------------|-----------------------------|------|-------|---------------|-------|---------|
| Symbol                            | Parameter                         | Test conditions             | Rate |       |               |       | Unit    |
|                                   |                                   |                             | 25°C |       | -40°C to 85°C |       |         |
|                                   |                                   |                             | min  | max   | min           | max   |         |
| Vh                                | Hysteresis voltage                | Vcc=5.0V                    | 0.2  | 0.9   | 0.2           | 1.0   | V       |
| Von                               | On(operation)voltage              | Vo ≤ 0.1VloL<br>≤ 20 uA     |      | 2.4   |               | 2.3   |         |
| Voff                              | Off(dropout)voltage               | Vo ≥ Vcc-01VloH<br>≤ -20 uA | 0.8  |       | 0.9           |       |         |
| VoL                               | Output low voltage                | loL=3.2 mA<br>Vcc=4.5V      | -    | 0.3   |               | 0.4   |         |
| VoH                               | Output high voltage               | loH=-1.0 mA<br>Vcc=4.5V     | 3.6  |       | 3.5           | -     |         |
| RI                                | Input resistance                  | Vcc=5.0V                    | 3.0  | 7.0   | 3.0           | 7.0   | kOhm    |
| Transmitter electrical parameters |                                   |                             |      |       |               |       |         |
| Symbol                            | Parameter                         | Test conditions             | Rate |       |               |       | Unit    |
|                                   |                                   |                             | 25°C |       | -40°C to 85°C |       |         |
|                                   |                                   |                             | min  | max   | min           | max   |         |
| VoL                               | Output low voltage                | Vcc=4.5V<br>VH=2.0V         | -    | -5.2  |               | -5.0  | V       |
| VoH                               | Output high voltage               | Vcc=4.5V<br>VL=0.8V         | 5.2  |       | 5.0           | -     |         |
| I                                 | Input low current                 | Vcc=5.5V Vπ=0V              | -    | -1.0  |               | -10.0 | uA      |
| IH                                | Input high current                | Vcc=5.5V<br>VH=Vcc          |      | 1.0   |               | 10.0  |         |
| SR                                | Speed of output frontchange       | Vcc=5.0V CL=50<br>-1000 pF  | 3.0  | 30    | 2.7           | 27    | V/uS    |
| Ro                                | Output resistance                 | Vcc=V+=V-=0V<br>Vo=±2V      | 350  | -     | 300           | -     | Ohm     |
| Isc                               | Short circuit outputcurrent       | Vcc=5.5V<br>Vo=0V           |      | -5050 |               | -6060 | mA kbps |
| ST                                | Speed of information transmission | Vcc=4.5V<br>CL=1000 pF      | 140  |       | 150           | -     |         |



### Dynamic parameters

| Symbol           | Parameter                        | Test conditions        | Rate |      |               |      | Unit |
|------------------|----------------------------------|------------------------|------|------|---------------|------|------|
|                  |                                  |                        | 25°C |      | -40°C to 85°C |      |      |
|                  |                                  |                        | min  | max  | min           | max  |      |
| tPHLR<br>(tPLHR) | Signal propagation<br>delay time | Vcc=4.5V<br>CL=150 pF  |      | 9.7  | -             | 10   | us   |
| tPHLT<br>(tPLHT) | Signal propagation<br>delay time | Vcc=4.5V<br>CL=2500 pF |      | 5.0* |               | 6.0* |      |

### Capacitance

| Symbol | Parameter           | Test conditions | Rate |     |               |     | Unit |
|--------|---------------------|-----------------|------|-----|---------------|-----|------|
|        |                     |                 | 25°C |     | -40°C to 85°C |     |      |
|        |                     |                 | min  | max | min           | max |      |
| CIN    | Input capacitance   | 5.0             | 9.0  |     |               |     | pF   |
| CpD    | Dynamic capacitance |                 | 90   |     |               |     |      |

### Static parameters

| Symbol          | Parameter                  | Test conditions                          | Rate |      |               |     | Unit |
|-----------------|----------------------------|------------------------------------------|------|------|---------------|-----|------|
|                 |                            |                                          | 25°C |      | -40°C to 85°C |     |      |
|                 |                            |                                          | min  | max  | min           | max |      |
| I <sub>cc</sub> | Consumption current static | V <sub>cc</sub> =5.0V V <sub>π</sub> =0V |      | 10.0 |               | 14  | mA   |




| Truth table |                                                |   |   |
|-------------|------------------------------------------------|---|---|
| Inputs      | RIn,TIN                                        | H | L |
| Outputs     | RovT,TovT                                      | L | H |
| H-vol-L     | Note:<br>Itage high level;<br>ow voltage level |   |   |

## Order information

| Order Number     | Package | Package Quantity      | Marking<br>On The park | Temperature    |
|------------------|---------|-----------------------|------------------------|----------------|
| ADM232AANZ-TUDI  | DIP16   | Tube,25,A box of 1000 | ADM232AANZ             | - 40°C to 85°C |
| ADM232AARNZ-TUDI | SOP16   | Tape,Reel,2500        | ADM232AA               |                |
| ADM232AARWZ-TUDI | SMD16   | Tape,Reel,1000        | ADM232AA               |                |







## Package SOP16



| SIZE<br>SYMBOL | MIN./mm    | MAX./mm |
|----------------|------------|---------|
| A              | 9.80       | 10.00   |
| A1             | 0.356      | 0.456   |
| A2             | 1.27TYP    |         |
| A3             | 0.302TYP   |         |
| B              | 3.85       | 3.95    |
| B1             | 5.84       | 6.24    |
| B2             | 5.00 TYP   |         |
| C              | 1.40       | 1.60    |
| C1             | 0.61       | 0.71    |
| C2             | 0.54       | 0.64    |
| C3             | 0.05       | 0.25    |
| C4             | 0.203      | 0.233   |
| D              | 1.05 TYP   |         |
| D1             | 0.40       | 0.70    |
| D2             | 0.15       | 0.25    |
| R1             | 0.20TYP    |         |
| R2             | 0.20TYP    |         |
| 01             | 8°~12°TYP4 |         |
| 02             | 8°~12°TYP4 |         |
| 03             | 0°~8°      |         |
| 04             | 4°~12°     |         |






## Package SMD16



| SIZE<br>SYMBOL | MIN./mm | MAX./mm |
|----------------|---------|---------|
| A              | —       | 2.65    |
| A1             | 0.10    | 0.30    |
| A2             | 2.25    | 2.35    |
| A3             | 0.97    | 1.07    |
| D              | 10.10   | 10.50   |
| E              | 10.26   | 10.60   |
| E1             | 7.30    | 7.70    |
| e              | 1.27BSC |         |
| L              | 0.55    | 0.85    |
| L1             | 1.4BSC  |         |
| H              | 0.345   | 0.365   |
| R              | 0.20TYP |         |
| R1             | 0.30TYP |         |
| θ              | 0°      | 8°      |
| θ 1            | 45° TYP |         |
| 02             | 12° TYP |         |
| 03             | 0°      | 8°      |
| 04             | 0°      | 10°     |

## Package DIP16



| SIZE<br>SYMBOL | MIN./mm | MAX./mm |
|----------------|---------|---------|
| A2             | 3.20    | 3.60    |
| A1             | 0.51    | —       |
| A              | 3.60    | 5.33    |
| L              | 3.00    | 3.60    |
| b              | 0.36    | 0.56    |
| B1             | 1.52    |         |
| D              | 18.80   | 19.94   |
| E1             | 6.20    | 6.60    |
| e              | 2.54    |         |
| C              | 0.20    | 0.36    |
| eB             | 7.62    | 9.30    |
| R              | 0.20TYP |         |
| R1             | 0.30TYP |         |
| $\theta$       | 0°      | 8°      |
| $\theta 1$     | 45°TYP  |         |
| 02             | 12°TYP  |         |
| 03             | 0°      | 8°      |
| 04             | 0°      | 10°     |



## Important statement:

- TUDI Semiconductor reserves the right to modify the product manual without prior notice! Before placing an order, customers need to confirm whether the obtained information is the latest version and verify the completeness of the relevant information.
- Any semi-guide product is subject to failure or malfunction under specified conditions. It is the buyer's responsibility to comply with safety standards when using TUDI Semiconductor products for system design and whole machine manufacturing. And take the appropriate safety measures to avoid the potential in the risk of loss of personal injury or loss of property situation!
- TUDI Semiconductor products have not been licensed for life support, military, and aerospace applications, and therefore TUDI Semiconductor is not responsible for any consequences arising from the use of this product in these areas.
- If any or all TUDI Semiconductor products (including technical data, services) described or contained in this document are subject to any applicable local export control laws and regulations, they may not be exported without an export license from the relevant authorities in accordance with such laws.
- The specifications of any and all TUDI Semiconductor products described or contained in this document specify the performance, characteristics, and functionality of said products in their standalone state, but do not guarantee the performance, characteristics, and functionality of said products installed in Customer's products or equipment. In order to verify symptoms and conditions that cannot be evaluated in a standalone device, the Customer should ultimately evaluate and test the device installed in the Customer's product device.
- TUDI Semiconductor documentation is only allowed to be copied without any alteration of the content and with the relevant authorization. TUDI Semiconductor assumes no responsibility or liability for altered documents.
- TUDI Semiconductor is committed to becoming the preferred semiconductor brand for customers, and TUDI Semiconductor will strive to provide customers with better performance and better quality products.