Eaton 16D27Q

Fuse-link, LV, 16 A, AC 500 V, D2, gR, IEC, fast acting

PRODUCT NAME	Eaton Bussmann series low voltage D fuse
CATALOG NUMBER	16D27Q
UPC	051712831710
PRODUCT LENGTH/DEPTH	50 mm
PRODUCT HEIGHT	22 mm
PRODUCT WIDTH	22 mm
PRODUCT WEIGHT	28.24 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	IEC 60269 EAC DIN EN 60269-3 (VDE 0636 Part 30) DIN EN 60269-1 (VDE 0636 Part 10) DIN VDE 0636-301

Powering Business Worldwide

□□□□	
AMPERAGE RATING	16 A
FUSE SIZE	DII
BREAKING CAPACITY	50 kA
CONSTRUCTION SIZE (FUSE INSERTS)	DII
RATED VOLTAGE AC	500 V
CLASS	Class gR
FUSE TYPE	D27Q - Fast acting
UTILIZATION CATEGORY	gR (general purpose semiconductor protection)
ACCESSORY/SPARE PART TYPE	16GD27 Grey screw cap gauge piece
COLOR	Gray
INTERRUPT RATING	50 kAIC
FUSE INDICATOR	Non-indicating
CONNECTION	Other
CONSTRUCTION	D2
CONSTRUCTION SIZE	DII
FUSE SHAPE	Bottle
RESPONSE TIME	Fast-acting
SUITABLE FOR	E27/DII Fuse base TFD27 Fuse base screw fixing SFRD27 Fuse base DIN-Rail mount TFRD27 Fuse base DIN-Rail mount
MATERIAL	White ceramic body
PACKAGING TYPE	Standard
RELEASE CHARACTERISTIC	Fast (F)
VOLTAGE RATING	500 V
TYPE	Fuse
SPECIAL FEATURES	Fast-acting
APPLICATION	For domestic and general industrial applications

□□	
DECLARATIONS OF CONFORMITY	eaton-low-voltage-d-fuse-declaration-of-conformity-uk251016en.pdf

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□