Eaton 50D33R

Eaton Bussmann series low voltage D fuse, Ultra-rapid, 500V, 50A, Non Indicating, fuse, Class gR, Ultra rapid, White, Ceramic body

PRODUCT NAME	Eaton Bussmann series low voltage D fuse
CATALOG NUMBER	50D33R
UPC	051712835626
PRODUCT LENGTH/DEPTH	50 mm
PRODUCT HEIGHT	27 mm
PRODUCT WIDTH	27 mm
PRODUCT WEIGHT	52.16 g
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	IEC 60269 VDE DIN EN 60269-3 (VDE 0636 Part 30) DIN EN 60269-1 (VDE 0636 Part 10) DIN VDE 0636-301

Powering Business Worldwide

□□□□	
AMPERAGE RATING	50 A
FUSE SIZE	DIII
BREAKING CAPACITY	50 kA
CONSTRUCTION SIZE (FUSE INSERTS)	DIII
RATED VOLTAGE AC	500 V
CLASS	Class gR
FUSE TYPE	D33R - Ultra rapid
UTILIZATION CATEGORY	gR (general purpose semiconductor protection)
ACCESSORY/SPARE PART TYPE	50GD33 White screw cap gauge piece
COLOR	White
INTERRUPT RATING	50 kAIC
FUSE INDICATOR	Non-indicating
CONNECTION	Other
CONSTRUCTION	D3
CONSTRUCTION SIZE	DIII
FUSE SHAPE	Bottle
RESPONSE TIME	Ultra rapid
SUITABLE FOR	E33/DIII Fuse base TFD33 Fuse base screw fixing SFRD33 Fuse base DIN-Rail mount TFRD33 Fuse base DIN-Rail mount
MATERIAL	White ceramic body
RELEASE CHARACTERISTIC	Super fast (FF)
QUANTITY	25
VOLTAGE RATING	500 V
TYPE	fuse
SPECIAL FEATURES	Ultra-rapid
APPLICATION	For domestic and general industrial applications

□□	
DECLARATIONS OF CONFORMITY	eaton-low-voltage-d-fuse-declaration-of-conformity-uk251016en.pdf

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□