# Eaton 12OHGMA20

Oil fuse-link, medium voltage, 20 A, AC 12 kV, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker

| | |
|---|---|
| **PRODUCT NAME** | Eaton Bussmann series medium voltage oil fuse |
| **CATALOG NUMBER** | 12OHGMA20 |
| **UPC** | 051712585811 |
| **PRODUCT LENGTH/DEPTH** | 359 mm |
| **PRODUCT HEIGHT** | 63.5 mm |
| **PRODUCT WIDTH** | 63.5 mm |
| **PRODUCT WEIGHT** | 2600 g |
| **COMPLIANCES** | BS 2692-1<br>ESI 12-8 |
| **CERTIFICATIONS** | IEC Rated<br>IEC60282-1<br>KEMA |

Powering Business Worldwide

## □□□□

| | |
|---|---|
| **AMPERAGE RATING** | 20 A |
| **FUSE INDICATOR** | with striker |
| **FUSE SIZE** | 63.5 x 359 mm |
| **BREAKING CAPACITY** | 40 kA |
| **INSTALLATION TECHNIQUE** | Oil |
| **PERFORMANCE CAT ACCORDING TO IEC 60282-1** | Back-up |
| **PRODUCT APPLICATION** | Primary side transformer protection |
| **RATED FREQUENCY - MAX** | 60 Hz |
| **RATED FREQUENCY - MIN** | 50 Hz |
| **RELEASE CHARACTERISTIC** | Other |
| **STANDARD** | British Standard |
| **UTILIZATION CATEGORY** | Other |
| **VOLTAGE TYPE** | AC |
| **WITH STRIKER** | Yes |
| **FUSE DIAMETER** | 63.5 mm |
| **JOULE INTEGRAL (I2T) - MAX OPERATING** | 5 x 103 |
| **JOULE INTEGRAL (I2T) - MIN PRE-ARCING** | 3.4 x 102 |
| **RESISTANCE** | 77 |
| **CLASS** | Class back-up |
| **BARRELS** | 1 |
| **CONSTRUCTION TYPE** | F02/BS 2692 |
| **FUSE SHAPE** | Cylindrical |
| **INTERRUPT RATING** | 40 kAIC |
| **CONSTRUCTION SIZE** | 63.5 x 359 mm |
| **VOLTAGE RATING** | 12 kV |
| **TYPE** | fuse |
| **APPLICATION** | protection of primary side transformer, and oil-filled fuse switch combination unit |
| **FUSE TYPE** | OHGM |

## □□

| | |
|---|---|
| □□□□: | |
| □□□□: | |
| □□□: | |
| □□: | |

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□