



SPECIFICATIONS

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+105℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Housing LCP UL94V-0 Natural
Contacts Brass/Sn-plated

Circuit	Part NO.	Dimensions mm		
		A	B	C
2	HC-PH-2AWD-LCP-04	2.00	4.90	6.00
3	HC-PH-3AWD-LCP-04	4.00	6.90	8.00
4	HC-PH-4AWD-LCP-04	6.00	8.90	10.00
5	HC-PH-5AWD-LCP-04	8.00	10.90	12.00
6	HC-PH-6AWD-LCP-04	10.00	12.90	14.00
7	HC-PH-7AWD-LCP-04	12.00	14.90	16.00
8	HC-PH-8AWD-LCP-04	14.00	16.90	18.00
9	HC-PH-9AWD-LCP-04	16.00	18.90	20.00
10	HC-PH-10AWD-LCP-04	18.00	20.90	22.00
11	HC-PH-11AWD-LCP-04	20.00	22.90	24.00
12	HC-PH-12AWD-LCP-04	22.00	24.90	26.00
13	HC-PH-13AWD-LCP-04	24.00	26.90	28.00
14	HC-PH-14AWD-LCP-04	26.00	28.90	30.00
15	HC-PH-15AWD-LCP-04	28.00	30.90	32.00
16	HC-PH-16AWD-LCP-04	30.00	32.90	34.00

Ordering Information

HC-PH- N*** - LCP - * - 04

Pin

Type

Colour

数量/本色

数量/黑色

数量/白色

数量/蓝色

数量/黄色

数量/绿色

数量/红色

数量/紫色

数量/棕色

数量/灰色

数量/银色

数量/金色

数量/铜色

数量/锡色

数量/镍色

数量/铬色

数量/钴色

数量/铋色

数量/锑色

数量/钨色

数量/钼色

数量/铌色

数量/钽色

数量/铌色

数量/钽色

	GENERL TOLERANCE		制图	04				
			DIM TOL	审核				
1	初版发行		X.X ±0.30	批准	产品名称	PH(2.0) 单排 定位弯针	版本	A
			X.XX ±0.20	CHECK	TITLE		REV.	
			X.XXX ±0.10	比例	产品料号	HC-PH-NAWD-LCP-04	单位	mm
			Angle ±3.0°	SCALE	PART NO.		UNITS	
序号	变更内容	日期	投影	投影	材料		页次	1/1
No.	MODIFY CONTENT	MODIFY DATE	Projection	Projection	MATERIAL		SHEET	