Eaton 170E3587

Eaton Bussmann series high speed traction fuse, 160 A, 750 V, gR (general purpose semiconductor protection), compact size 1, slotted center bolted tags

PRODUCT NAME	Eaton Bussmann series high speed traction fuse
CATALOG NUMBER	170E3587
UPC	051712209298
PRODUCT LENGTH/DEPTH	129 mm
PRODUCT HEIGHT	61 mm
PRODUCT WIDTH	43 mm
PRODUCT WEIGHT	942 g
COMPLIANCES	RoHS Compliant IEC

Powering Business Worldwide

□□□□	
AMPERAGE RATING	160 A
BREAKING CAPACITY	100 kA
VOLTAGE TYPE	DC
UTILIZATION CATEGORY	gR (general purpose semiconductor protection)
INSULATED METAL GRIPPING LUGS (IMGL)	No
FUSE INDICATOR	Other
FUSE SIZE	1*
CLASS	Class gR
WATT LOSSES	26 W
FUSE SHAPE	Square body, slotted center bolted tags
PRE ARC (I2T)	7700
MOUNTING DIMENSION	M8
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	156 mm
CURRENT TYPE	DC
RATED VOLTAGE DC	750 V
COLOR	None
INTERRUPT RATING	100 kAIC
CONSTRUCTION SIZE	Other
PACKAGING TYPE	Standard
VOLTAGE RATING	750 V
TYPE	Fuse
APPLICATION	traction
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

□□	
DECLARATIONS OF CONFORMITY	eaton-high-speed-square-body-fuse-declaration-of-conformity-uk251153en.pdf

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□