







Poles		04	05	06	07	08	09	10	11	12	13
Dim L		20	25	30	35	40	45	50	55	60	65
Dim P		15	20	25	30	35	40	45	50	55	60
TOL		±0.10			±0.15			±0.20			
Poles	14	15	16	17	18	19	20	21	22	23	24
Dim L	70	75	80	85	90	95	100	105	110	115	120
Dim P	65	70	75	80	85	90	95	100	105	110	115
TOL	±0.20		±0.30				±0.35				

SIGN	DATE	DESCRIPTION	APPROVER
△	9/1'09	The solid block changed from 2~24P to 4~24P.	Kind
△	09/30'10	Add the Fillet	Tason
△	09/30'10	The design is changed	Tason
△	09/30'10	The Safety Approval "UL" to "cULus"	Tason
△	10/14'10	Steel to Brass stamping	Tason
△	02/15'11	Add the "tuv" Safety Approval	Tason
△	03/11'14	The dimension is changed from 4.0mm to 3.7mm	Guoxue
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Material:

- Item① Terminal housing:Thermoplastic (UL 94V-0)
- Item② Terminal body:Brass stamping Tin plated,△
- Item③ Wire guard:Stainless steel
- Item④ Terminal screw: Steel Zinc plating"+/-"slot type

Electrical cULus TUV

- Voltage rating: 300VAC250VAC
- Current rating: 8A/12A
- Wire range:
 - Solid wire(AWG): 14-26/0.2-2.5mm
 - Stranded wire(AWG): 14-26/0.2-2.5mm
- Torque: 3.5Lb-In/0.4Nm
- Screw: M2.5
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C/ -40°C to +105°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:
- Critical dimension:

T3 xx 04 x 4 xxxx G

	Color	
△ 04 4 POLES	0 Black (RAL9005)	0000 "@"logo RoHS compliant
05 5 POLES	2 Red (RAL3001/D)	000A "ANY"logo (lead<4%)
...	3 Orange(RAL2011/P)	Customer Request In copper Alloy
24 24 POLES	4 Yellow(RAL1018/A)	
	5 Green(RAL6018/T)	
	6 Blue (RAL5015/A)	
	8 Grey(RAL7035/D)	
	C Green(RAL6018/U)	

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	T3 5.0 Series solid block type						
PART NO.	T3xx04x4xxxxG			DWG NO.	8T30201		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
		Guoxue 2014.03.11	Guoxue 2014.03.11		UNIT: mm	X. ±0.50	
					SCALE: NONE	X.X ±0.30	
						X.XX ±0.10	
						X° ±1°	
SHEET: 01/01				REV.: G			